



SETTING STANDARDS IN HAULING™

Everything You Need ...  
and the **Power**  
to do **More!**



**WRECKER • 8T-INTEGRATED**

**8-Ton Wrecker: 8T-INT**

[www.dancoproducts.com](http://www.dancoproducts.com)

MADE IN THE USA • GREENCASTLE, PA



- 4,000 lb (1,814.37 kg) Wheel Lift
- Safety Chain Storage Pockets



- Hydraulic Stiff Legs w/ Adjustable Feet

**OPTIONS\***

- Clutch Pump or PTO/Pump
- Planetary Winches
- Wrecker Special Light Bar
- Tow Dollies & Brackets
- Custom Paint
- Front Push Bumper
- Rear View Camera
- Tunnel Tool Box Options
- Wheel Simulators
- Additional LED Lighting

**SPECIFICATIONS**

**RECOVERY BOOM**

|   |           |            |             |
|---|-----------|------------|-------------|
| Boom Rating at Boom Swivel                        | Retracted | 16,000 lb  | 7,257.48 kg |
|   | Extended  | 8,000 lb   | 3,628.74 kg |
| Maximum Angle                                     |           | 35 Degrees |             |
| Lift Height from Ground to Hook at Max. Elevation | Retracted | 105-7/8 in | 268.92 cm   |
|   | Extended  | 134-1/2 in | 341.63 cm   |
| Reach Past Tail-Board Minimum Elevation           |           | 58-3/4 in  | 149.23 cm   |
| Reach Past Tail-Board Maximum Elevation           |           | 30-1/2 in  | 77.47 cm    |

**UNDERLIFT**

|   |           |            |             |
|---|-----------|------------|-------------|
| Lift Capacity at Full Extension                 |           | 4,000 lb   | 1,814.37 kg |
| Range of Tilt                                   | Up        | 71 Degrees |             |
|   | Down      | 22 Degrees |             |
| Distance from Bumper to Center Line of Lift Arm | Retracted | 51 in      | 129.54 cm   |
|   | Extended  | 80-5/8 in  | 204.79 cm   |
| Tow Rating                                      |           | 7,500 lb   | 3,401.94 kg |

**WINCH & CABLES**

|  |                 |                   |
|--|-----------------|-------------------|
| Winch Rating: 1st Layer of Each Drum/Winch | 8,000 lb        | 3,628.74 kg       |
| Cable Diameter and Length Each Drum        | 3/8 in x 100 ft | 0.95 cm x 30.48 m |

**CHASSIS RECOMMENDATIONS**

|  |               |              |
|--|---------------|--------------|
| Cab to Axle                            | 60 in         | 152.40 cm    |
| Cab to Axle: 24" (60.96 cm) Tunnel Box | 84 in         | 213.36 cm    |
| Minimum GVWR                           | 15,000 lb     | 6,803.89 kg  |
| Maximum GVWR                           | 26,000 lb     | 11,793.40 kg |
| Minimum Frame RBM                      | 280,000 in-lb |              |

**STANDARD FEATURES**

- Integrated Boom & Underlift System
- 60" (152.40 cm) Aluminum Body
- Right & Left Side Tool Compartments
- Right & Left Side Manual Controls
- Dual Ramsey Worm Gear Winches
- Cable Tensioners
- Winch Free Spool Handles
- Rear Hydraulic Stiff Legs
- Adjustable Stiff Leg Feet
- LED STT Lights in Pylon
- Junction Box & Wiring Harness
- Tool Box Lighting
- 1 Pr Low Mount LED Work Lights
- Frame Fork Holders
- Low Mount D-Rings
- 1 Set of Frame Forks & Receivers
- Receptacle for Tow Lights
- Lift Arm Storage Pockets
- Safety Chain Storage Pockets
- Full Height Enclosed Pylon
- Federal Standard #108 Lighting
- Mud Flaps

**IMPORTANT:** Gross vehicle rating limitation must be considered. Ratings are based on structural factors only, not chassis capacity. Danco specifications shown are approximations and may vary depending on chassis selected. Prices and product specifications are subject to change without notice. Optional equipment may be shown in photographs and may not be part of the standard package. Optional upgrade prices not included in standard pricing. See [dancoproducts.com](http://dancoproducts.com) for a more complete list of specifications. \* Optional upgrade prices not included in standard pricing. All prices are installed, Freight on Board Greencastle, PA

DISTRIBUTED BY:

**DANCO PRODUCTS**

411 South Cedar Lane  
Greencastle, PA 17225  
Telephone: 717-597-7185  
Toll-free in US 1-800-453-2626  
[www.dancoproducts.com](http://www.dancoproducts.com)



Wrecker\_8T-INT\_05272020