

High Performance Redefined



SETTING STANDARDS IN HAULING™



WRECKER • 8T-INTEGRATED SELF-LOADER

8-Ton Wrecker: 8TSL-INT

www.dancoproducts.com

MADE IN THE USA • GREENCASTLE, PA



• Self-Loader Wheel-Lift System



• Rear Electronic Switch Controls & Wireless Remote

OPTIONS*

- Clutch Pump or PTO/Pump
- Planetary Winches
- Wrecker Special Light Bar
- Tow Dollies & Brackets
- Custom Paint
- Front Push Bumper
- Rear View Camera
- Tunnel Tool Box Options
- Wheel Simulators
- Additional LED Lighting

SPECIFICATIONS

RECOVERY BOOM

Boom Rating at Boom Swivel	Retracted	16,000 lb	7,257.48 kg
	Extended	8,000 lb	3,628.74 kg
Maximum Angle		35 Degrees	
Lift Height from Ground to Hook at Max. Elevation	Retracted	105-7/8 in	268.92 cm
	Extended	134-1/2 in	341.63 cm
Reach Past Tail-Board Minimum Elevation		58-3/4 in	149.23 cm
Reach Past Tail-Board Maximum Elevation		30-1/2 in	77.47 cm

UNDERLIFT

Lift Capacity at Full Extension		4,000 lb	1,814.37 kg
Range of Tilt	Up	71 Degrees	
	Down	22 Degrees	

Distance from Bumper to Center Line of Lift Arm

Retracted	51 in	129.54 cm
Extended	80-5/8 in	204.79 cm

Tow Rating

	7,500 lb	3,401.94 kg
--	----------	-------------

WINCH & CABLES

Winch Rating: 1st Layer of Each Drum/Winch	8,000 lb	3,628.74 kg
Cable Diameter and Length Each Drum	3/8 in x 100 ft	0.95 cm x 30.48 m

CHASSIS RECOMMENDATIONS

Cab to Axle	60 in	152.40 cm
Cab to Axle 24" (60.96 cm) Tunnel Box	84 in	213.36 cm
Minimum GVWR	15,000 lb	6,803.89 kg
Maximum GVWR	26,000 lb	11,793.40 kg
Minimum Frame RBM	280,000 in-lb	

STANDARD FEATURES

- Integrated Boom & Underlift System
- Self-Loader Wheel Lift System
- 180 Degree Pivoting Crossbar
- Self-Centering Crossbar
- Aluminum Modular Body
- Right & Left Side Tool Compartments
- Dual Ramsey Worm Gear Winches
- Cable Tensioners
- Winch Free Spool Handles
- Trailer Hitch Adapter
- Rear Hydraulic Stiff Legs
- Adjustable Stiff Leg Feet
- Right & Left Side Electric Controls
- Wireless Remote Control
- Safety Chain Storage Pockets
- Full Height Enclosed Pylon
- LED STT Lights in Pylon
- Federal Standard #108 Lighting
- Junction Box & Wiring Harness
- Tool Box Lighting
- Low Mount D-Rings
- 1 Pr Low Mount LED Work Lights
- Receptacle for Tow Lights
- Mud Flaps

IMPORTANT: Gross vehicle rating limitation must be considered. Ratings are based on structural factors only, not chassis capacity. Danco specifications shown are approximations and may vary depending on chassis selected. Prices and product specifications are subject to change without notice. Optional equipment may be shown in photographs and may not be part of the standard package. Optional upgrade prices not included in standard pricing. See dancoproducts.com for a more complete list of specifications. * Optional upgrade prices not included in standard pricing. All prices are installed, Freight on Board Greencastle, PA

DISTRIBUTED BY:

DANCO PRODUCTS

411 South Cedar Lane
Greencastle, PA 17225
Telephone: 717-597-7185
Toll-free in US 1-800-453-2626
www.dancoproducts.com



Wrecker_8TSL_05272020