



SETTING STANDARDS IN HAULING™

12-Series Low Approach Car Carrier: 12SLA

www.dancoproducts.com

MADE IN THE USA • GREENCASTLE, PA



• Wheel Grid • Lift Arm Storage • Ball-Mount Plate



• Dual Angle Low Approach Deck

OPTIONS*

- PTO & Pump Options
- 102 in (259.08 cm) Deck Width
- Diamond Plate Deck
- Additional Deck Tie Downs
- Cab Protector / Frame Mount
- Enclosed Cab Protector Bottom
- Side-Winding Cab Protector
- Additional Side Marker Lights
- Chrome Bezel Marker Lights
- Light Package in Cab Protector
- Tool Box Options
- Light Bar (10 Head LED)
- Wireless Remote Winch
- Planetary Winch
- Magnetic Tow Lights
- Cable Roller Guide
- Additional Work Lights
- Chains & Straps
- Wheel Simulators

SPECIFICATIONS	DECK LENGTH		CAB TO AXLE (clear)	
	19 ft	5.79 m	114 - 120 in	289.56 - 304.80 cm
	19.5 ft	5.94 m	120 - 126 in	304.80 - 320.04 cm
	20 ft	6.10 m	120 - 132 in	304.80 - 335.28 cm
	21 ft	6.40 m	138 - 144 in	350.52 - 365.76 cm
	21.5 ft	6.55 m	144 - 150 in	365.76 - 381.00 cm
	22 ft	6.71 m	150 - 156 in	381.00 - 396.24 cm
	Deck Capacity (Water Level Load)	12,000 lb	5,443.11 kg	
	Deck Width (outside)	96 in	243.84 cm	
	Smooth Decking	3/16 in	0.48 cm	
	Crossmember Spacings on Center	8 in	20.32 cm	
	Winch Ramsey Worm Gear	8,000 lb	3,628.74 kg	
	Winch Cable	3/8 in x 50 ft	0.95 cm x 15.24 m	
	WHEEL LIFT			
	Lift Capacity	4,000 lb	1,814.37 kg	
	Tow Capacity	7,500 lb	3,401.94 kg	
	CHASSIS RECOMMENDATIONS			
	Minimum GWR (Gross Vehicle Weight Rating)			
	With Wheel Lift	19,500 lb	8,845.05 kg	
	Without Wheel Lift	15,000 lb	6,803.89 kg	
	Minimum RBM	500,000 in-lb		
	Minimum Frame Height	29 in	73.66 cm	
	Maximum Frame Height	38 in	96.52 cm	

STANDARD FEATURES

- Dual Angle Low Approach Deck
- Removable Deck Rails
- Tie Downs: 4 Front · 2 Middle · 4 Rear
- Finish: Painted Black Acrylic Enamel
- Undercoat on Under-Side of Deck
- Heavy Duty Approach Plate
- Right & Left Chain Trays
- Cable Tensioner
- Manual Shift Winch Free Spool Lever
- Anti-Tilt Deck Feature
- Extra Length Push-Off Cylinder
- Two Outboard Power Lift Cylinders
- Right & Left Illuminated Controls
- Counterbalance Valves
- High Performance Slide Pads
- Rear Safety Chain Storage Pockets
- Adjustable Deck Hold Downs
- Lubrication Fittings at Pivot Points
- Federal Standard #108 Lighting
- LED Light Package
- Weather Resistant Electrical System
- Deck & Subframe Junction Boxes
- Two Pair of LED Work Lights
- Receptacle for Tow Lights
- Back-Up Lights & Alarm
- Wheel Lift Grids & Arms
- Ball Mount Plate
- Strap Hooks
- Lift Arm Storage Brackets
- Mud Flaps

IMPORTANT: Gross vehicle rating limitation must be considered. Ratings are based on structural factors only, not chassis capacity. Danco's body ratings are based on a water level capacity. Danco specifications shown are approximations and may vary depending on chassis selected. Prices and product specifications are subject to change without notice. Consult with state and local laws for the maximum vehicle lengths allowed. Optional equipment may be shown in photographs and may not be part of the standard package. Optional upgrade prices not included in standard pricing. See dancoproducts.com for a more complete list of specifications. * Optional upgrade prices not included in standard pricing. All prices are installed, Freight on Board Greencastle, PA

DISTRIBUTED BY:

DANCO PRODUCTS
 411 South Cedar Lane
 Greencastle, PA 17225
 Telephone: 717-597-7185
 Toll-free in US 1-800-453-2626
www.dancoproducts.com

