You



Greater Visibility, Reduces Blind Spots for Drivers.



Engineered for Greater Load Distribution and Stability.

### **OPTIONS\***

- PTO & Pump Options
- 102 in (259.08 cm) Main Deck
- Additional Deck Tie Downs
- Polished Deck Rails • Removable Main Deck Rails
- · Additional Side Marker Lights
- Tool Box Options
- Wireless Remote Winch
- Beacon Lights
- Magnetic Tow Lights
- Additional Work Lights
- · Chains & Straps
- Wheel Simulators

### LENGTH

20 ft 6.10 m 21 ft 6.40 m 22 ft 6.71 m

Width: Tie Downs: 2 Front • 2 Middle • 4 Rear

Capacity (Water Level Load):

Winch Ramsey Worm Gear: Winch Cable:

#### **LENGTH**

13.5 ft 4.11 m Capacity (Water Level Load): Width:

Tie Downs: 4 Front • 2 Middle • 4 Rear Winch Ramsey Worm Gear:

# Winch Cable: WHEEL LIFT

Lift Capacity: 4 000 lb 1,814.37 kg Tow Capacity: 7,500 lb 3,401.94 kg

CAB TO AXLE (clear)

120 - 132 in

138 - 144 in

150 - 156 in

12,000 lb

8.000 lb

5,000 lb

8.000 lb

3/8 in x 75 ft

96 in

3/8 in x 50 ft

96 in

## **CHASSIS RECOMMENDATIONS**

Minimum GVWR: 26,000 lb 11,793.40 kg Maximum GVWR: 33,000 lb 14,968.55 kg Minimum RBM: (each rail) 600,000 in-lb Minimum Frame Height: 29 in 73.66 cm Maximum Frame Height: 38 in 96.52 cm Wheel/Tire Size: 19.5/22.5 in

#### STANDARD FEATURES

- Extruded Aluminum Deck
- Non-Polished Deck Finish
- Non-Removable Deck Rails
- Heavy Duty Approach Plate
- Cat Walk on Upper Deck
- Tie Downs: 4 Front 4 Middle 4 Rear
- Anti-Tilt Deck Feature
- Wheel Lift Grids & Arms
- Slide Behind Tire Bars

- Ball Mount Plate
- Right & Left Illuminated Controls

• Lift Arm Storage Brackets

• Extra Length Push-Off Cylinder

• 2 Power Lift Cylinders (main Deck)

• 2 Power Lift Cylinders (upper Deck)

- Counterbalance Valves
- High Performance Slide Pads • Rear Safety Chain Storage Pockets
- Adjustable Deck Hold Downs
- Lubrication Fittings at Pivot Points • Extension Ladder
- Federal Standard #108 Lighting • LED Light Package
- Weather Resistant Electrical System

304.80 - 335.28 cm

350.52 - 365.76 cm

381.00 - 396.24 cm

5,443.11 kg

3,628.74 kg

2,267.96 kg

243.84 cm

3,628.74 kg

.95 cm x 22.86 m

.95 cm x 15.24 m

243.84 cm

- Plastic Track System for Hoses & Wires
- Deck & Subframe Junction Boxes
- Two Pair of LED Work Lights
- Three Pair of Side Marker Deck Lights
- Receptacle for Tow Lights
- Back-Up Lights & Alarm
- Mud Flaps

Ratings are based on structural factors only, not chassis capacity. Danco's body ratings are based on a water level capacity. Danco specifications

IMPORTANT: \*Max 26,000 lb (11,793.39 kg) GVWR to stay under standard CDL restrictions. Gross vehicle rating limitation must be considered. shown are approximations and may vary depending on chassis selected. Prices and product specifications are subject to change without notice Consult with state and local laws for the maximum vehicle lengths allowed. Optional equipment may be shown in photographs and may not be part of the standard package. Optional upgrade prices not included in standard pricing. See dancoproducts.com for a more complete list of specifications. \* Optional upgrade prices not included in standard pricing. All prices are installed, Freight on Board Greencastle, PA



411 South Cedar Lane Greencastle, PA 17225 Telephone: 717-597-7185 Toll-free in US 1-800-453-2626 www.dancoproducts.com

