

## Product

## Type

### DieselAid D

Deposit Control

### Diesel Fuel Additive

**Contains a polymeric dispersant in high flash aromatic solvent designed to diminish deposit build up in diesel fuel engines**

## Application

DieselAid D is a deposit control additive for use in low-sulphur diesel fuels, marine distillate and other middle distillate ground fuels suffering or likely to suffer from traditional and IDID deposit build up. It is not suitable for use in aviation fuels. It will not cause plunger-sticking of in-line pumps and will not interact with lubricants or other fuel additives. It will also provide protection against corrosion and will show benefits in terms of fuel quality including fuel stability

## Physical Characteristics

Appearance	Yellow Liquid
Viscosity at 40 Deg C	17mm <sup>2</sup> /s
Viscosity at 20 Deg C	33mm <sup>2</sup> /s
Density at 15 Deg C	910 kg /m <sup>3</sup>
Flash Point	>60 Deg C
Pour Point	> - 15 Deg C

## Dosage Rate

DieselAid D is recommended at 1 litre per 6,000 litres of fuel

## Packaging

DieselAid D is supplied in 1, 5, 25 litre containers and 200 litre barrels

## Handling

DieselAid D should be stored away from heat, sparks and open flame. Ensure the product is always stored and used at temperatures above -3 Deg C. If it is accidentally stored at extremely low temperatures below -5 Deg C, crystallisation may occur. If this happens re-store the product at room temperature (above 0 Deg C) for 24 hours and agitate the contents by shaking the bottle or rolling the drum as appropriate. The product will then be fit for use.

## Safety & First Aid

Always consult the MarShip UK Material Safety Data Sheet (MSDS) for safety information before using the product

The information contained in this document is provided free of charge and is based on technical data that MarShip UK believes to be reliable. It is intended for use by persons having technical skill and their own discretion and risk. MarShip UK accepts no liability for any loss, damage or expense arising from or in connection with the use of the information. Furthermore, none of the contents of this publication should be taken as a licence to operate under any patent nor as a recommendation to infringe any patent

### **Storage & Handling on Board**

DieselAid D should be stored away from heat, sparks and open flame. Please ensure the product is always stored at temperatures above -3 Deg C. If it is accidentally stored at extremely low temperatures below -5 Deg C, crystallisation may occur. If this happens re-store the product at room temperature (above 0 Deg C) for 24 hours and agitate the contents by shaking the bottle or rolling the drum as appropriate. The product will then be fit for use.

### **Technical Service & Product Ordering**

Please contact MarShip UK on + (0) 1666 818791 or email us [sales@marship.eu](mailto:sales@marship.eu)

---

The information contained in this document is provided free of charge and is based on technical data that MarShip UK believes to be reliable. It is intended for use by persons having technical skill and their own discretion and risk. MarShip UK accepts no liability for any loss, damage or expense arising from or in connection with the use of the information. Furthermore, none of the contents of this publication should be taken as a licence to operate under any patent nor as a recommendation to infringe any patent