

Product

| Type

DieselAid® LDB

Lubricity, Deposit Control and Broad Spectrum Biocide

Diesel Fuel Additive

An all-round treatment designed to offset the adverse effects of ULSD. Blended for operations where Diesel is held in tanks but not stored for excessive periods. DieselAid® LDB adds lubricity, reduces and prevents fuel system deposits whilst the biocide reduces the risk of yeast growth and Diesel Bug. A multifunctional blend to ensure engine efficiency and fuel consumption is maintained.

Application

DieselAid® LDB is a combined treatment to counter the effects of ULSD. Lubricity, deposit control and biocide for use in ultra low-sulphur diesel fuels, marine distillate and other middle distillate ground fuels having poor lubricity characteristics and suffering or likely to suffer from traditional and IDID deposit build up . It will also provide protection against corrosion and will show benefits in terms of fuel quality including fuel stability. The broad spectrum biocide will kill and prevent the growth of yeast, moulds and bacteria (aka Diesel-Bug).

Physical Characteristics

Appearance	Dark Brown Liquid
Viscosity at 40 Deg C	60 mm /s ²
Viscosity at 20 Deg C	80 mm /s ²
Density at 15 Deg C	900 kg /m ³
Flash Point	>65 Deg C
Pour Point	-15 > -Deg C

Dosage Rate

DieselAid LDB is recommended at 1 litre per 4,000 litres of fuel

Packaging

DieselAid LDB is supplied in 1, 5, 25 litre containers and 200 litre barrels

Handling

DieselAid LDB should be stored away from heat, sparks and open flame. MarShip recommends the use of Neoprene or nitrile gloves and safety glasses. If product has been stored below the pour point temperature it should be heated to 21 degrees C before using.

Safety & First Aid

Always consult the MarShip Material Safety Data Sheet (MSDS) for safety information before using the product

Technical Service & Product Ordering

Please contact MarShip on + (0) 1666 818 791 or email us sales@marship.eu

The information contained in this document is provided free of charge and is based on technical data that MarShip believes to be reliable. It is intended for use by persons having technical skill and their own discretion and risk. MarShip accepts no liability for any loss, damage or expense arising from or in connection with the use of the information. Furthermore, none of the contents of this publication should be taken as a licence to operate under any patent nor as a recommendation to infringe any patent