

| Product | Type |
|---------|------|
|---------|------|

DieselAid® C
 For Long Standing Stored fuel

Diesel Fuel Additive
Multifunctional diesel fuel additive designed to stabilise and demulsify fuel, reduce and prevent fuel injection system deposits, improve fuel lubricity, increase cetane number and contains a broad spectrum biocide to prevent microbial attack.

Application

DieselAid C is a complete fuel protection additive for long standing or stored fuel which prevents fuel degradation. Containing the following additives to maintain fuel in good condition ensuring engines start when most needed.

- Fuel Stabiliser:** Replaces the stabiliser that is added by the fuel manufacturer that normally lasts a maximum of 6 months.
- Lubricity:** Replaces the lubricity lost when the Sulphur was removed.
- Deposit Control:** Cleaning injection system of traditional and newer IDID deposits from low Sulphur fuel.
- Cetane Improver:** Degrading fuel loses this all important cetane rating which ensures easy starting. A critical requirement in an emergency engine.
- Demulsifier:** Fuel is hygroscopic (Biofuel 30 times more so) with the ever changing environment at sea from cold to hot and dry to humid climates water ingress has to be regularly drained.
- Broad Spectrum Biocide:** To counter microbial attack in stored (standing) fuel from bacteria, moulds and yeasts.

Six highly important additives to ensure your fuel and fuel system is kept in optimum condition.

Physical Characteristics

| | Minimum | Target | Maximum |
|---------------------------|---------|-----------|---------|
| Flash point, C, PMCC | | 79 | |
| LBS par U.S. Gal @15.6 C | | 7.92 | |
| LBS per IMP Gal @15.6 C | | 9.51 | |
| Pour Point | | -51 Deg C | |
| Specific Gravity @ 15.6 C | 0.930 | 0.950 | 0.970 |
| Viscosity @ 40 C, CST | | 6 | |

Dosage Rate

DieselAid C is recommended at 1 litre per 2,000 litres of fuel

Packaging

DieselAid C is supplied in 1, 5 and 25 litre containers and 200 litre barrels

The information contained in this document is provided free of charge and is based on technical data that MarShip believes to be reliable. It is intended for use by persons having technical skill and their own discretion and risk. MarShip accepts no liability for any loss, damage or expense arising from or in connection with the use of the information. Furthermore, none of the contents of this publication should be taken as a licence to operate under any patent nor as a recommendation to infringe any patent

Handling

DieselAid C contains the cetane improver 2ethylhexyl nitrate (EHNM). Special care should be taken in the handling and use of this product.

Safety & First Aid

Always consult the MarShip UK Material Safety Data Sheet (MSDS) for safety information before using the product

Technical Service & Product Ordering

Please contact MarShip UK on + (0) 1666 818791 or email us sales@marship.eu

The information contained in this document is provided free of charge and is based on technical data that MarShip UK believes to be reliable. It is intended for use by persons having technical skill and their own discretion and risk. MarShip UK accepts no liability for any loss, damage or expense arising from or in connection with the use of the information. Furthermore, none of the contents of this publication should be taken as a licence to operate under any patent nor as a recommendation to infringe any patent