








REKOLA

Rekola Reflex AbrasiveSoft cloth



Product code	Color code	Dimension	
10-7050	4 colour tags	55 x 23 cm	Rekola Reflex AbrasiveSoft cloth Multiple-use 86 grs
Packed	5 pcs pp bag 	30 pcs 5-pack per transport box	
Where:	Hard top and ceramic safety floors for hygienic cleaning results: e.g. toilet and bathroom facilities at healthcare, nursery, school, university, office, public building, hospitality and residential areas. Floors at sport facilities, food industry, locker rooms etc.		
How:	<p>In conjunction with Rekola Reflex 50 cm squeegee and Rekola Reflex 100/180 extendable handle.</p> <p>For preparation on a cleaning trolley charge cloths in a closed container such as a 6 Ltr. rectangle bucket with lid. Put the cloths inside and pour the desired fluid equally over the cloths, leave for a while with closed lid.</p> <p>Alternatively charge cloths in a washing machine, by adapting the spin cycle of the final rinse.</p> <p>Avoid overdosing, bleach and softeners.</p>		
Charge:	<p>With clean water; optional diluted with UMF suitable chemical according to manufacturer's instructions.</p> <p><i>Please be aware that some chemicals may cause damage to user, material and environment.</i></p> <p>Depending on floor circumstances charge the cloths with 100-180 ml per cloth; Regardless of the charging liquid: avoid overdosing.</p>		
Eco Labeled:	 3083 0027		

REKOLA

Maintenance	
Laundry:	   
Washing:	Rinse twice to ensure all cleaning chemicals are removed. Main program for synthetic fibers at 95°C, for environmental reasons at 60° C or less is preferred Rinse twice to ensure all laundry agents are removed. Adjust temperatures and water volumes accordingly.
	Tumble dry at low heat.
	Do not use bleach or softener.
	Low water level during processing or overloading washing machine (max 80% of door window) may cause irreversible damage to cloths.
Disinfection:	Non -bleach disinfectant* laundry agent and autoclaving may be used if required *e.g. peroxide based; this may affect colors.
Durability:	500 washing cycles. Rough surfaces like safety flooring will reduce lifetime expectations
Disposable:	Rekola Reflex AbrasiveSoft cloths are purely synthetic: may be used for recycling programs; or because of their high energy value and with no emissions other than CO ₂ and water can be safely disposed by controlled energy-supply programs.
Components	
Body:	50% split Ultra Microfiber and 50 % PET film 90% PES 10 PA and F= 0,154 Dtex.
Borders:	100% PES.
Characteristics	
Shrinkage:	< 5% at recommended washing instructions.
Color fastness	4-5. <i>standard request ≥ 3-4</i>
Charging	4,2 DAC value. <i>standard request minimum 2,5</i>
Abrasion	The abrasion generated during use, is not advised for use on softer material surfaces; such as Polycarbonates.
Weber & Leucht S301/1.3 dirt removal	Ceramic Tile SF 11 Dust A23 Damp 93% <i>standard request ≥ 70</i> PVC- Flooring PL-03 Dust A23 Damp 87% <i>standard request ≥ 70</i> Ceramic Tile SF 11 Muddy dirt A05 Damp 100% <i>standard request ≥ 70</i> PVC- Flooring PL-03 Muddy dirt A05 Damp 100% <i>standard request ≥ 70</i>
Bacteria reduction	E-coli 99,89% log 2,96 S.aureus 99,31 log 2,16
Non-Touch	In conjunction with Rekola Reflex squeegee tool, dirty cloths are not touched when demounting.
Patent:	FI2010000028 Floor Maintenance Device and Cloth.
Guarantee	
500 times use and wash in general hygiene cleaning circumstances at a maintained non-safety sealed floor. Extended usage can be achieved if optimal laundry and cleaning conditions are considered. For instruction and details ask your distributor.	