



ESG SERIES 2000

PERFORMANCE BY DESIGN

The ESG Series 2000 is supported by a solid, high-quality welded chassis. It is highly configurable with multiple heights as well as a variety of cabinet accessories.

- Fully welded frame
- 2500 lbs static-load capacity
- 1750 lbs dynamic-load capacity
- Adjustable rack-mount rails
- Concealed hinge doors with locking swinghandles
- Doors open 140° and have 81% mesh for air flow
- Upgradeable to electronic access

CONFIGURABLE

The ESG Series 2000 is fully configurable with an array of customization options, such as, but not limited to:

- Side panels
- Interchangeable top and bottom panels
- Adjustable PDU rails and vertical cable management mounts
- Caster kits
- Two- and three- bay retrofitting
- Airflow or solid doors
- Split doors available for single bay
- Single, two, and three bay configurations
- Factory assembled to order

AFFORDABLE

Aggressively priced to compete with current market offerings.

ECO-FRIENDLY

Coated with an eco-friendly reflective white paint, the ESG Series 2000 will reduce energy costs and footprint of any data center, IT facility, or other mission critical environment. Other standard rack finishes available.

AMERICAN-MADE

The ESG Series 2000 is American-made at the e-Systems Group factory in upstate New York.

e-Systems Consoles
FEATURING EDP AND SMC

19" CABINET HEIGHTS AND FRAME DEPTHS

- 42U
- 45U
- 48U
- 51U
- 42 inch
- 48 inch

BAY CONFIGURATIONS AND DOOR OPTIONS

- One Bay*
- Two Bays
- Three Bays

- 81% Mesh
- Split*
- Solid

STATIC/DYNAMIC LOAD-BEARING CAPACITY

- 4-Post Fully Welded Frame
- Static - 2500 lbs.
- Dynamic - 1750 lbs.

All cabinets include leveling feet; casters optional for all configurations.

TOP AND BOTTOM PLATES

- Specify Open (No Panels)
- Solid
- Multi 6" Round Grommets
- Lateral Cable Trough

SIDE PANELS

- (1) Full Length Exterior
- (1) Full Length Interior
- (1 pair) Split Exterior
- (1 pair) Split Interior

ACCESSORIES

- PDU/ Cable Management Plate
- Vertical air seals
- Anti- Tip/Stabilizer
- Interior Top RM Air Seal
- Base Ext. Air Seal - 24"W, 42"W , 48"W
- Cable Chimney (On Multiple Bays)
- Grounding Kit

