



Drum Heater Jackets with Digital Control — High Temperature Metal Drum

Argus Heating design, manufacture, and distribute a range of IBC and drum heaters and accessories.

The high temperature metal drum heater jackets are specifically designed for high temperature applications. The insulated exterior minimises heat loss and a compact digital temperature controller ensures that you have an easy, efficient and economical method of heating and maintaining the temperature of your product. Optional insulated lid available. **Caution:** for metal drum applications only.

Drum heater jacket with insulated lid and digital temperature controller.



Other products in the range.

Features

- Metal drum heating jackets to suit 25, 50, 105, and 200L drums and products that can safely be raised to high temperatures.
- The jackets are fitted with a digital temperature controller, providing precise control from 0-200°C.
- Manufactured and tested in accordance with AS/NZS 3100.
- The approximate warm-up duration is 24 hours to raise 200L of water from +15°C to +80°C with a 1200W drum heater. Custom design heater jackets available on request.

Applications

Typically used to heat:

- Greases
- Fats
- Adhesives
- Chemicals
- Oils
- Paints
- Coatings
- Cosmetics

Construction

Durable high temperature silicone/glass fabric outer. Glass filament insulation. High temperature silicone heating cable. Easy quick-release buckles. Water resistant polycarbonate enclosed digital controller with a two metre power cord and moulded 3-pin plug.

| Stock code | Description | Drum type (L) | Dimensions (mm) | Wattage (W) | Voltage (V) |
|-------------------|---------------|---------------|-----------------|-------------|-------------|
| DH121 (ex-stock) | 0-200°C | 200 | 1990 x 800 | 1200 | 230 |
| DH221 | 0-200°C | 200 | 1990 x 800 | 1200 | 110 |
| DH122 | 0-200°C | 200 | 1990 x 800 | 1500 | 230 |
| DH130 | 0-200°C | 105 | 1650 x 370 | 700 | 230 |
| DH230 | 0-200°C | 105 | 1650 x 370 | 700 | 110 |
| DH131 | 0-200°C | 50-60 | 1330 x 460 | 440 | 230 |
| DH231 | 0-200°C | 50-60 | 1330 x 460 | 440 | 110 |
| DH132 | 0-200°C | 20-30 | 1200 x 400 | 380 | 230 |
| DH232 | 0-200°C | 20-30 | 1200 x 400 | 380 | 110 |
| FAB009 (ex-stock) | Insulated Lid | 200 | 600mm diameter | N/A | N/A |