



ACOUSTICAL CEILING & WALL PANELS

DIRECT ATTACHED INTERIOR PANEL

Standard wood fiber interior panels are perfect for churches, restaurants, schools – anywhere an economical solution to noise is needed. These panels are lightweight and resist abuse. They can easily be installed in new construction or in an existing building for effective sound control, achieving a Noise Reduction Coefficient (NRC) of up to 1.00.

All panels are available in square and beveled edge treatments. Beveled edge panels are recommended in any situation where two Cardinal Acoustics panels come in contact with each other.

CARDINAL STANDARD INTERIOR PANELS SPECIFICATION DETAILS:

EDGE DETAIL	NRC	THICKNESS	WIDTH	LENGTH	WEIGHT P/SF
Bevel/Bevel, Bevel/Square, Square/Square	.45 – .80	5/8"	24" or 48"	48" up to 96"	1.55
	.60 – .95	1"			2.20
	.70 – 1.0	1 ½"			3.42



For more information, visit cardinalacoustics.com
or call us at 614.721.3001

Email: info@cardinalacoustics.com

CORPORATE OFFICES
2941 Donnylane Blvd.
Columbus, OH 43235

WAREHOUSE AND FABRICATION PLANT
721 Springfield Street
Dayton, Ohio 45403