

ELEGANT ACOUSTICAL SOLUTION

Direct Attached panels are an optimal cost-effective solution for a variety of environments and spaces. They are easily installed for effective sound control in new construction or an existing building.

We recommend beveled edge panels where two panels are in contact with each other.

All Cardinal Acoustics ceiling panels meet the requirements of ASTM E1264 Type XIV, pattern F, Class A as tested in accordance to ASTM E84.

APPLICATIONS

- Schools
- Restaurants
- Churches
- Gymnasiums
- Corporate offices
- Shooting ranges

FEATURES

- NRC up to 0.95
- Lightweight
- Thinner profile
- Lifetime warranty
- Abuse-resistant
- Class A fire rating

For more information, visit cardinal acoustics.com or call us at 614.721.3001

Email: info@cardinalacoustics.com

OFFICE HEADOUARTERS


2941 Donnylane Blvd. Columbus, OH 43235

MANUFACTURING & FABRICATION PLANT

2000 S. Yellow Springs St. Springfield, OH 45506







EDGE DETAIL	NRC	THICKNESS	WIDTH	LENGTH	WEIGHT P/SF
Bevel/Bevel, Bevel/Square, Square/Square	.45 – .80	5/8"	23-3/4" or 48"	48" up to 96"	1.55
	.60 – .95	1"			2.20
	.70 – .80	1 1/2"			3.42









FINISH OPTIONS

Cardinal Direct Attached Panels are available in painted natural, painted white, and can be customized to match colors of all paint manufacturers.

For more information, visit cardinalacoustics.com or call us at 614.721.3001

Email: info@cardinalacoustics.com

OFFICE HEADQUARTERS

2941 Donnylane Blvd. 2000 S. Yellow Springs St. Columbus, OH 43235 Springfield, OH 45506

MANUFACTURING & FABRICATION PLANT



