

# Remu

Pipeline Brochure  
ENG



## PADDING BUCKETS

PD 3160, PD 2160, EX 140

REMU Oy Finland

Tel: +358 20 743 1160

Mail: [info@remu.fi](mailto:info@remu.fi)

[www.remu.fi](http://www.remu.fi)

# PADDING BUCKETS

Fulfilling requirements and overcoming challenges of pipeline projects, trench backfilling and other demanding heavy duty applications.

## MEET THE STANDARDS

Blade spacing 24 mm (1") gives you a grain size of 16 mm (5/8") that is normally required for padding material. In addition there is numerous blade models and spacing available.

## EASY TO USE

No special skills are needed to operate the bucket. A short introduction to good screening practice is all that's needed to put this powerful tool to work for you.

## FRAME THAT LASTS

Designed for roughest use where wear and tear together with pulling large rock is just daily matter.

## POWER TRANSMISSION YOU CAN TRUST

PD buckets have direct drive piston motors for each rotor to divide the power of the base machine more evenly, giving better operating efficiency and fuel savings.

## MINIMAL MAINTENANCE

Daily field maintenance means checking just one service point, and the motor side of the bucket requires no daily maintenance at all.

**20** YEARS PUSHING THE INDUSTRY STANDARDS

**10** YEARS EXPERIENCE WORKING WITH THE USA PIPELINERS

**3** SPECIALLY DESIGNED BUCKETS FOR PIPELINE PADDING



**PD 3160**

FOR CLASS 300 EXCAVATORS



**EX 140**

FOR CLASS 200 EXCAVATORS



**PD 2160**

FOR CLASS 250 EXCAVATORS

# Remu

PD 3160

TECHNICAL DATA	METRIC	IMPERIAL
Volume (ISO)	2 m <sup>3</sup>	2,6 yd <sup>3</sup>
Screening area	1,5 m <sup>2</sup>	16 ft <sup>2</sup>
Width	2140 mm	84 inch
Depth	1660 mm	65 inch
Height	1600 mm	63 inch
Maximum allowed pressure	300 bar	4500 PSI
Maximum allowed flow	220 l/min	58 Gal/min
Weight	2930 kg	6460 lbs

PD 2160

TECHNICAL DATA	METRIC	IMPERIAL
Volume (ISO)	1,4 m <sup>3</sup>	1,8 yd <sup>3</sup>
Screening area	1m <sup>2</sup>	11 ft <sup>2</sup>
Width	2140 mm	84 inch
Depth	1660 mm	65 inch
Height	1340 mm	53 inch
Maximum allowed pressure	300 bar	4500 PSI
Maximum allowed flow	200 l/min	53 Gal/min
Weight	2600 kg	5732 lbs

EX 140

TECHNICAL DATA	METRIC	IMPERIAL
Volume (ISO)	0,9m <sup>3</sup>	1,2 yd <sup>3</sup>
Screening area	0,8 m <sup>2</sup>	8,6 ft <sup>2</sup>
Width	1256 mm	50 inch
Depth	1156 mm	46 inch
Height	1394 mm	55 inch
Maximum allowed pressure	210 - 250 bar	3050 - 3650 PSI
Maximum allowed flow	150 - 230 l/min	40 - 60 Gal/min
Weight	1650 kg	3638 lbs

## REMU OY

Inhantie 7  
 FI-63700 Ähtäri  
 Tel / +358 20 743 1160  
 Mail / info@remu.fi

## REMU USA INC.

8 Hemlock St  
 Old Orchard Beach ME 04064  
 Maine - USA  
 Tel / +1 888 600 0018  
 Mail / usa@remu.fi

## DEALER INFO

