

## ARTIGO RUBBER FLOORING FIRE CLASS

COMPLIES WITH NZ BUILDING CODE CLAUSES C<sub>1</sub> – C<sub>6</sub> PROTECTION FROM FIRE

PRODUCT	ISO 9239-1 CLASS	CRF RESULT	DoP
<b>RIGATO</b>	C <sub>fl</sub> – s1	≥ 4.5 kW/m <sup>2</sup>	0987-cpd-26
<b>GRAIN</b>	B <sub>fl</sub> – s1	≥ 8.0 kW/m <sup>2</sup>	0987-cpd-16 rev.1
<b>GRANITO</b>	B <sub>fl</sub> – s1	≥ 8.0 kW/m <sup>2</sup>	0987-cpd-16 rev.1
<b>SCREED</b>	C <sub>fl</sub> – s1	≥ 4.5 kW/m <sup>2</sup>	0987-cpr 170 rev.1
<b>ZEUS</b>	B <sub>fl</sub> – s1	≥ 8.0 kW/m <sup>2</sup>	0987-cpd-16 rev.1
<b>NATURA</b>	C <sub>fl</sub> – s1	≥ 4.5 kW/m <sup>2</sup>	0987-cpr-16 rev.1
<b>UNI</b>	B <sub>fl</sub> – s1	≥ 8.0 kW/m <sup>2</sup>	0987-cpd-22
<b>KAYAR</b>	B <sub>fl</sub> – s1	≥ 8.0 kW/m <sup>2</sup>	0987-cpd-22
<b>BS CLASSIC</b>	B <sub>fl</sub> – s1	≥ 8.0 kW/m <sup>2</sup>	0897-cpd-75/182
<b>ZERO.4</b>	B <sub>fl</sub> – s1	≥ 8.0 kW/m <sup>2</sup>	0897-cpd-75/182
<b>BS STRONG</b>	B <sub>fl</sub> – s1	≥ 8.0 kW/m <sup>2</sup>	0897-cpd-75/182
<b>ROLLFLOOR</b>	C <sub>fl</sub> – s1	≥ 4.5 kW/m <sup>2</sup>	0897-cpd-09
<b>FULL STEP</b>	B <sub>fl</sub> – s1	≥ 8.0 kW/m <sup>2</sup>	0897-cpd-75/182