



POLYTEK SURFACE COATINGS FLOOR CARE INSTRUCTIONS

DAY OF INSTALLATION:

PLEASE STAY OFF YOUR FLOOR FOLLOWING THE INSTALLATION OF YOUR POLYTEK FLOOR! INSTALLERS WILL TYPICALLY BRING GARAGE DOORS DOWN ON SCREW OR GIVE INSTRUCTIONS ON WHEN IT IS SAFE TO CLOSE THE DOOR WHEN LEFT OPEN.

WHEN IS IT SAFE TO USE FOLLOWING INSTALLATION:

WALK-ON 6-8 HOURS

MOVE IN LIGHT OBJECTS: 12-14 HOURS

DRIVE-ON 24 HOURS

HEAVY OBJECTS: 24 HOURS

HOW TO CARE FOR YOUR FLOOR: (ONCE A WEEK)

ITS BEST PRACTICE TO SWEEP DEBRIS AND DIRT OFF YOUR FLOOR ON A REGULAR BASIS. THIS HELPS REDUCE DIRT BUILD UP AND KEEPS FROM DAILY GRINDING ON THE SURFACE. USE A PUSH BROOM OR LEAF BLOWER TO DO THIS.

DETERGENTS: (ONCE A MONTH)

WHEN USING A CLEANER OR DEGREASER ON THE COATED SURFACE, ITS BEST TO USE WARM WATER MIXED WITH THE CLEANING SOLUTION (CLR, SIMPLE GREEN, PINESOL) POUR DIRECTLY ON THE SURFACE AND USE A PUSH BROOM TO HELP LOOSEN ANY STUCK DEBRIS. (SCRUBBING THE SURFACE IS RECOMMENDED FOR VERY SOILED AREAS) LET SOLUTION SIT ON SURFACE AND THEN HOSE OUT OR PRESSURE WASH TO CLEAN THE SURFACE FURTHER. SQUEEGEE OR LET AIR DRY.

TAR, GLUE, PAINT:

USE A MILD SOLVENT OR GASOLINE ON THE SURFACE TO HELP BREAK DOWN THE CONTAMINANT. (MINERAL SPIRITS, ACETONE, XYLENE) SCRUBBING THE SURFACE WILL HELP BREAK DOWN THE PAINT OR GLUE.

THINGS TO WATCH OUT FOR:

BATTERY ACID, OVEN CLEANER, ACIDS, WELDING, AND HOT OBJECTS. BE SURE TO WIPE AND SPILLS AND MESSSES UP AS SOON AS YOU SEE THEM. GENERAL MAINTENANCE WILL PROLONG THE LIFE OF THE FLOOR!

Installer: _____ (P) _____