

Xcalibur™ E-line Jar

Protect against time-consuming and expensive stuck tool strings and fishing jobs in cased hole electrical line operations

Impact Selector's Xcalibur E-line wireline jar is a powerful yet cost effective way to reduce risk in electric wireline cased hole operations.

With the smaller cables used for cased hole operations there is often a very limited amount of overpull available to free stuck tools.

The Xcalibur jar acts to greatly increase the force available at the cablehead through using energy stored in compressed springs and the wireline itself to create a powerful upwards impulse on the tools.

As the force acts on the bottom of the jar, the cablehead is protected from the impact and remains unaffected.

The jar activation force can be easily adjusted at surface while in the string to account for different operations.

Available in a range of sizes and with all major types of mono-conductor connection, Xcalibur is ideal for most logging, perforating, pipe recovery and plug setting operations.



Features / Benefits

- ▶ Fully adjustable on the surface, while in the tool string.
- ▶ All mechanical design is unaffected by pressure or temperature.
- ▶ Accommodates various E-line connections.
- ▶ Maintenance can be performed in the field, within a confined space by a certified technician.
- ▶ Short, compact design; keeps rig ups as short as possible.
- ▶ Instant and unlimited activations with no waiting period once the pre-set activation force is reached.

Specifications

Diameter (inches)	.875	1.562	2.75
Max Temp (°F)	400	400	400
Max Pressure (psi)	25,000	25,000	25,000
Length (Closed / Open) (inches)	49.5 / 55.667	75.75 / 81.9375	59.47 / 65.87
Approximate Weight (lbs)	6	30	65
Field Adjustability (lbs)	100—1,000	300—1,400	400—1,700
Total Stroke (inches)	6.167	6.188	6.4
Power Stroke (inches)	5	4.875	4.5



IMPACT SELECTOR™
Intelligent Conveyance® Technologies



1-800-238-9239



impact@impactselector.com



www.impactselector.com



©Impact Selector – All rights reserved. August 2017