



## Mechanical Specifications

<b>Outside Diameter</b> (in / mm)	2.125 / 53.98	2.75 / 69.85
<b>Make-up Length</b> (in / mm)	29.625 / 752.48	32 / 813
<b>Weight</b> (lbs / kg)	22.3 / 10.12	38 / 17
<b>Upper and Lower Connections</b>	1-3/16"-12 UN (GO A)	1-5/8"-6 Acme (GO B)
<b>Fishing Method</b>	2.125" Overshot	2.75" Overshot

## Operational Specifications

<b>Pressure Rating</b> (psi / MPa)	25,000 / 172.4	25,000 / 172.4
<b>Temperature Rating</b> (°F / °C)	350 / 175 (explosives limited*)	350 / 175 (explosives limited*)
<b>Tensile Strength</b> (lbs)	50,000	100,000
<b>Shock Rating</b> (G)	5,000 3 Axis Minimum	5,000 3 Axis Minimum
<b>Maximum Moment Force</b> (Lb-Ft)	5,000**	7,000

\*Refer to explosives datasheet. Be careful to not exceed 300°F with RDX. HMX boosters are available.

\*\*Measured at center of tool. May vary due to field connections.

## Electrical Specifications

<b>Pass Through Voltage</b> (V)	600	600
<b>Pass Through Current</b> (A)	3	3

### Impact Selector's SPITFire™ Release Device

allows the wireline service company to reliably release the downhole tools in the event that the tool string becomes stuck in the wellbore. This avoids wire breaks, and facilitates the efficient and clean retrieval of the tool string using a conventional fishing overshot.

## Features and Benefits

- ▶ Ballistic Frangible Joint based tool.
- ▶ Tested with DynaEnergetics Dynaselect detonators, Austin A-140F detonators, and Teledyne Bridgewire detonators.
- ▶ High tensile strength.
- ▶ Compatible with jars.
- ▶ Compatible with Warrior Well Logging System and commercial perforating switches.
- ▶ Compatible with addressable and E.B. switches.
- ▶ Split ring allows removal and replacement of the detonator within minutes.

