



Designed solely to assist the driver by improving visibility and reducing known blind spots. This quad monitor can take up to 4 channels.

Used either as a reversing camera system, or combined with a nearside camera or our MDVR this monitor will benefit any fleet no matter what solution you choose.

Features

- FORS compliant
- 4 - Channel video inputs
- Screen select for single/double/triple/quad or H pattern.
- Adjustable views (true/mirror) and orientation



Sentinel Systems Ltd

Cotswold Airport, Kemble
Cirencester, Gloucestershire GL7 6BA

E: sales@sentinelsystems.co.uk
T: +44(0) 1285 771333





Specification

Technical Information

Screen Size	7" TFT (16:9)
Resolution	480 x 800
Power Supply	12v - 24v
Triggers	4
Channels	4 x 4 pin video inputs
Format	PAL/NTSC - CVBS only
Menu	By remote only - Contrast, brightness, colour, mirror/true/rotation, sound and language.
Audio	Yes
Split Channels	Mode options
Split Trigger	No
Brightness	300cd/m ²
IP Rating	Internal only
Operating Temperature	-20°C to +70°C
Storage Temperature	-30°C to +80°C
Other Features	n/a
Size	172mm x 48mm x 114mm
Mounting Options	Flush fit or fan bracket (multi-angle bracket)
Type Approval	E9 10R - 04 1283