



The Sentry S50 Series is a mobile digital video recorder equipped with the latest 1080P AHD recording technology.

Its simple practical design allows for easy installation and access when required, GPS and G-shock recording come as standard, bespoke alarm inputs and remote monitoring/download make this a multi-function package for any vehicle whether for an owner driver or large fleet.

Features

- Up to 1TB HDD
- Premium playback software supported on PC, IOS and android devices
- GPS, 3G, 4G and WiFi enabled
- 1080P and 720P High Definition ready
- Removable drive with secure key lock function to prevent unauthorised access
- Encrypted HDD with password protected data to support GDPR
- Supports 5 channels (4 x AHD and 1 x IP cameras)



Sentinel Systems Ltd

Cotswold Airport, Kemble
Cirencester, Gloucestershire GL7 6BA

E: sales@sentinelsystems.co.uk

T: +44(0) 1285 771333





Specification

System	Operating System	Linux
	Control Mode	Network (3G/4G/WIFI), Mouse or Access Unit
Video	Input	4 AHD Cameras + 1 IPC Cameras
	Output	1 CH Aviation
Audio	Input	4 AHD Cameras + 1 IPC Cameras
	Output	1 channel
Display	Display Split	1/4 Image display
	OSD	GPS information, alarm, acceleration, voltage, device information and many more
Recording	Video Compression	Video: H.264/H.265
	Image Resolution	PAL: 1080P(1920X1080), 720P(1280X720), WD1(928X576), WHD1(928X288), WCIF(464X288), D1(704X576), HD1(704x288), CIF(352x288) NTSC: 1080P(1920X1080), 720P(1280X720), WD1(928X480), WHD1(928X240), WCIF(464X240), D1(704x480), HD1(704x240),CIF(352x240); Digital: 1080P(1920X1080), 720P (1280X720)
	Recording Mode	Schedule/Alarm (sensor trigger, speed, acceleration, video loss)
	Search Mode	Date/time, channel, event
Network	3G/4G	Option to enable
	WIFI	802.11b/g/n
Locating	GPS	Location tracking, speed detection and time sync
Sensor	G-Sensor	Built-in X,Y and Z inertia sensor
Storage	HDD	1 x 2.5" SATA HDD
	Intercommunication	1 MIC interface
Power	Input	DC8-36V
	Output	5V@1A
Physical Characteristic	Dimension (L x W x H)	206mm x 170mm x 70.5mm (with bracket)
	Weight	1.24KG with HDD
Environment	Operating Temperature	-40°C to +70°C with heating and no HDD, -40°C to +55°C with heating and HDD
Approvals	Type Approval	E13 10R - 05 15244