



The Sentry S40 Series is a mobile digital video recorder equipped with the latest 1080P AHD recording technology and SD card recording.

Its compact and robust design allows for easy installation and access when required. GPS and G-shock recording come as standard, bespoke alarm inputs and remote monitoring/download make this a comprehensive package for any vehicle whether for an owner driver or large fleet.

Features

- Up to 256GB SD storage with back up mirror recording
- Premium playback software supported on PC, IOS and android devices
- GPS, 3G, 4G and WiFi enabled
- 1080P and 720P High Definition ready
- Removable drive with secure key lock function to prevent unauthorised access
- Supports 5 channels (4 x AHD and 1 x IP camera)



Sentinel Systems Ltd

Cotswold Airport, Kemble
Cirencester, Gloucestershire GL7 6BA

E: sales@sentinelsystems.co.uk

T: +44(0) 1285 771333





Specification

System	Operating System	Linux
	Control Mode	Network (3G/4G/WIFI), Mouse or Access Unit
Video	Input	4 AHD Cameras + 1 IPC Camera
	Output	1 CH Aviation
Audio	Input	4 AHD Cameras + 1 IPC Camera
	Output	1 channel
Display	Display Split	1/4/9 Image display
	OSD	GPS information, alarm, temperature, acceleration, voltage, device information and many more
Recording	Video Compression	Video: H.264
	Image Resolution	PAL: 1080P(1920X1080), 720P(1280X720), WD1(928X576), WHD1(928X288), WCIF(464X288), D1(704X576), HD1(704x288), CIF(352x288) NTSC: 1080P(1920X1080), 720P(1280X720), WD1(928X480), WHD1(928X240), WCIF(464X240), D1(704x480), HD1(704x240),CIF(352x240); Digital: 1080P(1920X1080), 720P (1280X720)
	Recording Mode	Schedule/Alarm (sensor trigger, speed, acceleration, video loss, temperature)
	Search Mode	Date/time, channel, event
Network	3G/4G	Option to enable
	WIFI	802.11b/g/n
Locating	GPS	Location tracking, speed detection and time sync
Sensor	G-Sensor	Built-in X,Y and Z inertia sensor
Storage	SD	Support SD 32GB/64GB/128GB – 2 SD card slots.
Power	Input	8-36V DC
	Output	5V@500mA
Physical Characteristic	Dimension (L x W x H)	167mm x 146mm x 54mm
	Weight	0.83 KG
Environment	Operating Temperature	-40°C to +70°C