



Our wireless camera system removes the need for challenging cable routing and can provide you the clear vision you need.

Features

- Waterproof monitor IP66 and IP69K Camera
- Auto pairing
- Wireless transmission range - 100m
- 720p AHD
- IR night vision - 5m
- Robust metal housing

Monitor

4
CH



IP
66

Camera

HD
720p

IP
69K



IR

Sentinel Systems Ltd

Unit 2, Querns Business Centre, Whitworth Road,
Cirencester, Gloucestershire GL7 1RT

E: sales@sentinelsystems.co.uk

T: +44(0) 1285 771333





Specification

Wireless Monitor Technical Information	Screen Size	7" High definition
	Resolution	1024 x 600
	Power Supply	10v - 32v
	Triggers	5 (Including Split)
	Channels	4 Wireless 2412 ~2467 MHz
	Format	AHD 720P
	Menu	Contrast, brightness, colour, mirror/true/rotation, sound, auto scan and language, volume.
	Audio	Yes
	Split Channels	Yes
	Split Trigger	Yes
	Brightness	600cd/m ²
	IP Rating	IP66
	Operating Temperature	-20°C to +70°C
	Storage Temperature	-30°C to +80°C
	Other Features	N/A
Size	190mm x 30mm x 130mm	
Mounting Options	U Bracket or fan bracket	
Wireless Camera Internal Electronics	Image Sensor	1/4" CMOS
	Format	AHD
	Pixels	1280 X 720
	Scanning System	Progressive Scanning
Technical Information	Resolution	720P
	Operating Temperature	-20°C to +70°C
	Storage Temperature	-30°C to +80°C
	Power Supply	12v
	Water Resistance	IP69K
	Viewing Angle	110°
	Audio	Yes
	Night Vision	3-5m
	AGC	Auto
	Electric Shutter	1/25(1/30) - 1/50,000 seconds
Type Approval	E13 10R - 05 15089	
Automotive Battery Technical Information	Power Supply Range	5-16V DC
	Battery Capacity	8700mAh /3.6V 4
	IP Rating	5V/12Hours 12V/4Hours
	Charging Time	Progressive Scanning
	Discharging Time	12-14 Hours (160-180mA@12V), 9 Hours (230mA)
	Temperatures	Charging Temp: -10 - 45°C 7. Working Temp: -20 - 60°C 8. Storage Temp: -20 - 60°C
	Dimensions	100.5mm x 64.5mm x 40.7mm
	Power Level Indicator	4 LEDs at a level of 25%, 50%, 75%, 100%.
	Mount	110° Magnetic