



TECHNICAL DATA

• Luminaire source	LED Smd
• Luminaire system wattage*	24W; 18W optional (VISION-6030) 32W; 18W/38W optional (VISION-1230/6060)
• Luminaire luminous flux*	1980lm ~ 4180lm
• Luminaire efficacy (avg.)	110lm/W
• Correlated colour temperature*	4000K, other CCT on request
• Colour rendering index	Ra ≥82
• Chromaticity tolerance	≤4 MacAdam
• Unified glare rating	UGR ≤16 ¹
• Beam	95°
• Service lifetime*	>50,000h L70/B10
• Ingress protection/resistance	IP40 / IK04
• Power factor	≥0.92
• Operating voltage	220-240V AC, 50/60Hz
• Operating temperature	-20°~45°C
• Protection class	II
• Finish	White trim (RAL 9003), opal diffuser
• Construction	Aluminium, PMMA
• Mounting	T-bar ceiling recessed, options below
• Warranty*	5 years
• Luminaire termination	Pre-wired 1.2m flex and plug
• Lighting control	Non dimmable ECG standard; TRIDONIC DALI/DSI, phase-cut dimming on request

ORDER DATA

Order code	Model	System wattage	Colour temp.	Luminous flux
16319104	VISION-1230-32W-4K	32W	4000K	3520lm
16319113	VISION-6060-32W-4K	32W	4000K	3520lm
16319122	VISION-6030-24W-4K	24W	4000K	2640lm

Specify **-18W** for 18W/1980lm option (VISION-1230/6060/6030)
Specify **-38W** for 38W/4180lm option (VISION-1230/6060)
Specify **-D** for DALI/DSI dimming; **-PD** for trailing/leading phase-cut dimming

ACCESSORIES

Order code	Model	Description
16316103	1230-PK-OS	Plaster kit, L1260xW360xH40mm (c/o 1210x310mm)
16316104	6060-PK-OS	Plaster kit, L660xW660xH40mm (c/o 610x610mm)
16316105	6030-PK-OS	Plaster kit, L660xW360xH40mm (c/o 610x310mm)
16316106	1230-SM	Surface mount frame, L1200xW355xH66mm
16316107	6060-SM	Surface mount frame, L600xW655xH66mm
16316108	6030-SM	Surface mount fame, L600xW355xH66mm

FEATURES

- Slim-line design, high efficiency and anti-glare
- High quality, high transperancy diffuser for optimal light output
- Multi switchable wattage, selectable via driver
- IPART and VEET accepted

OPTIONS/ACCESSORIES

- Multiple size, wattage & lumen packages
- Surface mount, plaster recess & suspension optional (kits required)
- TRIDONIC DALI/DSI, leading/trailing phase-cut dimming on request

