



# CM12 Dash Camera Datasheet

## Internet-Connected Front-Facing HD Camera Module



The CM12 is a high-definition, Internet-connected dash camera designed to improve fleet safety, exonerate drivers, and lower accident-related costs. A high-definition camera captures outward-facing video and automatically uploads footage of accidents, hard braking, and other events of interest. Samsara's intuitive cloud software provides video-based reports, driver scorecards, and search, enabling fleet operators to implement preventive safety coaching programs, prevent accidents, and lower costs.

### HIGHLIGHTS

- High definition outward-facing camera
- Automatic uploads footage of harsh driving events, plus on-demand retrieval
- Audio speaker for voice-based safety coaching
- Cloud-based reporting, accident reconstruction, and driver safety scorecards
- Easy to install, no hard-wiring into vehicle required
- Part of Samsara's complete platform for safety, fleet management, and compliance

# Technical Specifications

## Front-Facing Camera

|               |  |
|---------------|--|
| Field of view | 115° (semi-wide angle) front-facing camera |
| Resolution    | High definition (1080p)                    |
| Frame rate    | 30 fps                                     |
| Low light     | Optimized for low-light performance        |

## Audio Speaker

|                  |  |
|------------------|--|
| Built-in speaker | Inward-facing audio speaker for voice-based feedback during unsafe driving |
|------------------|--|

## Storage and Connectivity

|                  |   |
|------------------|---|
| Automatic upload | Automatically uploads video footage of harsh braking, cornering, acceleration, and crashes  |
| On-demand upload | Stores continues recordings on-camera, available for over-the-air retrieval on demand (stores most recent 24 hrs of driving time) |
| Connectivity     | High-speed 4G LTE wireless connectivity via Samsara VG-series gateways. Data secured via SSL (256-bit, military-grade encryption) |

## Mounting, Enclosure, and Power

|            |  |
|------------|--|
| Dimensions | Enclosure: 70 x 63 x 63 mm (2.7 x 2.5 x 2.5 in)<br>Cable: 4m (13 ft) |
| Mounting   | Mounts to windshield via industrial-grade adhesive tape (included)   |

|                              |  |
|------------------------------|--|
| <b>Power</b>                 | Connects to Samsara VG-series gateway via accessory port (power + data). No additional power source or wiring required |
| <b>Operating temperature</b> | -15 to 60° C   |

## Software Features

|                          |  |
|--------------------------|--|
| <b>Software features</b> | <p>Browser-based video playback in high definition from any Internet-connected device</p> <p>Safety incident reports, including accident reconstruction</p> <p>Driver safety rankings with score-cards</p> <p>On-demand retrieval (over the air) with proximity search</p> <p>Configurable audio coaching plays voice messages during unsafe driving (e.g. excessive speeding)</p> |
|--------------------------|--|

# Ordering Information

## CM Series Camera Modules

|         |                                      |
|---------|--------------------------------------|
| HW-CM12 | Samsara Front-Facing Dash Cam Module |
|---------|--------------------------------------|

## License

|                 |   |
|-----------------|---|
| LIC-CM1-ENT     | Enterprise license for single-camera CM-series modules, includes hosted software, cellular connectivity, ongoing software upgrades, maintenance, and support  |
| LIC-CM1-EXPRESS | Express license for single-camera CM-series, includes hosted software optimized for small-business fleets, cellular connectivity, ongoing software upgrades, maintenance, and support (Up to 20 units, additional limits apply) |

Note: Requires Samsara VG34 vehicle gateway, sold separately.