

Safety Data Sheet

SOLDER-IT UNDERCOATING WATER SOLUBLE PART # U-1G, U-5G, U-55G (XII)



SDS Revision Date:

03/19/2018

1. Identification

1.1. Product identifier :

Product Identity

SOLDER-IT™ Undercoating, Water Soluble Bulk, XII

Alternate Names

U-1G, U-5G, U-55

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

See Technical Data Sheet.

Application Method

See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name

SOLDER-IT, INC.
404 IRVINGTON STREET
PLEASANTVILLE, NY 10570 USA

Emergency

www.solderit.com

CHEMTEL (USA)

914-747-1092

24 hour Emergency Telephone No.

Customer Service: SOLDER-IT, INC.

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Skin Corr. 1B;H314

Causes severe skin burns and eye damage.

Eye Dam. 1;H318

Causes serious eye damage.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

Safety Data Sheet

SOLDER-IT UNDERCOATING WATER SOLUBLE PART # U-1G, U-5G, U-55G (XII)



SDS Revision Date:

03/19/2018

[Prevention]:

P260 Do not breathe mist / vapors / spray.

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P310 Immediately call a POISON CENTER or doctor / physician.

P363 Wash contaminated clothing before reuse.

[Storage]:

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Asphalt (petroleum) CAS Number: 0008052-42-4	25 - 50	Not Classified	[1][2]
Wollastonite CAS Number: 0013983-17-0	1.0 - 10	Skin Corr. 1B;H314 Eye Dam. 1;H318 STOT SE 3;H335	[1]
Bentonite CAS Number: 0001302-78-9	1.0 - 10	Not Classified	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

Safety Data Sheet

SOLDER-IT UNDERCOATING WATER SOLUBLE PART # U-1G, U-5G, U-55G (XII)



SDS Revision Date:

03/19/2018

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	If respiratory discomfort occurs, remove to fresh air. If discomfort continues, administer oxygen and get medical attention.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	If this product comes in contact with skin, remove material with mineral oil, then wash with soap and plenty of water.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview	No specific symptom data available. See section 2 for further details.
Eyes	Causes serious eye damage.
Skin	Causes severe skin burns and eye damage.

5. Fire-fighting measures

5.1. Extinguishing media

Carbon dioxide (CO₂), foam, or dry chemical. Water may be used to cool containers exposed to heat.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Combustion: carbon dioxide (CO₂), carbon monoxide (CO), nitrogen oxides, smoke, and fumes.

Do not breathe mist / vapors / spray.

5.3. Advice for fire-fighters

Material may foam if heated above 212F.

Minimize breathing vapors, gases or fumes of decomposition products. Do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

ERG Guide No. ----

Safety Data Sheet

SOLDER-IT UNDERCOATING WATER SOLUBLE PART # U-1G, U-5G, U-55G (XII)



SDS Revision Date:

03/19/2018

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Eliminate sources of ignition, and ventilate the area. Add sand or earth or absorb spill with suitable absorbent material and place in a closed container.

Keep product out of sewers and waterways by diking or impounding. Advise authorities if product has entered or may enter sewers or waterways. Assure conformity with applicable governmental regulations.

7. Handling and storage

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Do not freeze. Do not store in excess of 200F.

Incompatible materials: Strong oxidizing agents

Vapors are heavier than air and may travel along the ground or be moved by ventilation to locations distant from the point of material handling. To prevent fumes from entering buildings or confined areas, close all air intake sources near the material handling or the work area. To prevent ignition, avoid smoking, keep away from heat, open flames and sources of static or electrical sparking. Use explosion proof motors and equipment. Tank trucks or other containers should be grounded and/or bonded when the material is transferred.

Avoid prolonged or repeated inhalation of vapors or spray mists. Avoid prolonged or repeated skin contact. Adhere to good hygienic practices. Avoid open flames. Use with adequate ventilation.

Store in a cool, dry place, out of direct sunlight and away from heat, sparks, and flame.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

Health studies have shown that many petroleum hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

Safety Data Sheet

SOLDER-IT UNDERCOATING WATER SOLUBLE PART # U-1G, U-5G, U-55G (XII)



SDS Revision Date:

03/19/2018

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0001302-78-9	Bentonite	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0008052-42-4	Asphalt (petroleum)	OSHA	No Established Limit
		ACGIH	TWA: 0.5 mg/m ³ B
		NIOSH	Ca C 5 mg/m ³ [15-minute]
		Supplier	No Established Limit
0013983-17-0	Wollastonite	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0001302-78-9	Bentonite	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0008052-42-4	Asphalt (petroleum)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0013983-17-0	Wollastonite	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;

8.2. Exposure controls

Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes

Safety glasses or face shield for liquid material.

Skin

Solvent-resistant gloves.

Safety Data Sheet

SOLDER-IT UNDERCOATING WATER SOLUBLE PART # U-1G, U-5G, U-55G (XII)



SDS Revision Date:

03/19/2018

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Long sleeves and impervious clothing to protect against splashing. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Black Thixotropic Liquid
Odor	Not Measured
Odor threshold	Not Measured
pH	Not Measured
Melting point / freezing point	NA
Initial boiling point and boiling range	212F
Flash Point	None Unless water is removed
Evaporation rate (Ether = 1)	(Butyl Acetate=1)@77F: < 1
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured
Vapor pressure (Pa)	77F: 23.7mm of hg
Vapor Density	(Air=1): > 1
Specific Gravity	(H2O=1): 1.00 - 1.05
Solubility in Water	Soluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

Safety Data Sheet

SOLDER-IT UNDERCOATING WATER SOLUBLE PART # U-1G, U-5G, U-55G (XII)



SDS Revision Date:

03/19/2018

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Auto-ignition temperature unknown.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

No hazardous decomposition data available.

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Asphalt (petroleum) - (8052-42-4)	No data available	No data available	No data available	No data available	No data available
Wollastonite - (13983-17-0)	No data available	No data available	No data available	No data available	No data available
Bentonite - (1302-78-9)	No data available	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	1B	Causes severe skin burns and eye damage.
Serious eye damage/irritation	1	Causes serious eye damage.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable

Safety Data Sheet

SOLDER-IT UNDERCOATING WATER SOLUBLE PART # U-1G, U-5G, U-55G (XII)



SDS Revision Date:

03/19/2018

Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Asphalt (petroleum) - (8052-42-4)	Not Available	Not Available	Not Available
Wollastonite - (13983-17-0)	Not Available	Not Available	Not Available
Bentonite - (1302-78-9)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Safety Data Sheet

SOLDER-IT UNDERCOATING WATER SOLUBLE PART # U-1G, U-5G, U-55G (XII)



SDS Revision Date:

03/19/2018

14. Transport information

The description shown may not apply to all shipping situations. Consult 49 CFR, or appropriate regulations, for additional description requirements.

DOT Shipping Name: NON-Regulated
DOT Label Information: NA
DOT Hazard Class: NA
DOT Packing Group: NA

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification D2B E

US EPA Tier II Hazards

Fire: No
Sudden Release of Pressure: No
Reactive: No
Immediate (Acute): Yes
Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

Chromic acid, dipotassium salt

Proposition 65 - Developmental Toxins (>0.0%):

Chromic acid, dipotassium salt

Proposition 65 - Female Repro Toxins (>0.0%):

Chromic acid, dipotassium salt

Proposition 65 - Male Repro Toxins (>0.0%):

Safety Data Sheet

SOLDER-IT UNDERCOATING WATER SOLUBLE PART # U-1G, U-5G, U-55G (XII)



SDS Revision Date:

03/19/2018

Chromic acid, dipotassium salt

New Jersey RTK Substances (>1%):

Asphalt (petroleum)

Pennsylvania RTK Substances (>1%):

Asphalt (petroleum)

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

Disclaimer: This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The information has been completed to the best of our knowledge and is believed to be accurate and reliable as from the date indicated. However, no warranty is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy oneself as to the suitability and completeness of such information for his own particular use.

End of Document