

Product Information



1st Layer	Non-woven Pre Filter
2nd Layer	Cellulose Fiber
3rd Layer	Mono-filament Backer
Color	Black
Stake Distance	60 inches

Features

- Requires no chain linked fencing.
- Can be installed at a rate of 375 linear feet/hr.
- Relatively nothing can tear this geotextile, preventing common headaches associated with the maintenance of traditional & super silt fencing.
- Resists blinding.
- Acts as a dynamic filter-ponder; Siltron stands strong during dynamically changing storm water intensity.
- Performs well under hydraulic pressure.
- Compresses but decompresses as pressure alleviates. When a blinding slurry builds up, the compressed textile snaps back (about 5mm).
- Available in pre-staked bundles & master rolls.
- Pre-staked bundles are available in 50 ft intervals perfect for trenching; master rolls are available in 100 ft intervals for static slicing machines.
- Absorbs viscous pollutants carried in storm-water: motor oil, hydraulic fluid, diesel, etc.
- UV resistance numbers are much better than traditional silt fencing.

Product #	Description	Unit	Quantity	Shipping Weight
SIL-P 16	SILTRON 16 - PRE STAKED	LINEAR FT	50	575 lbs
SIL-M 16	SILTRON 16 - MASTER ROLL	LINEAR FT	150	575 lbs
SIL-P 21	SILTRON 21 - PRE STAKED	LINEAR FT	50	675 lbs
SIL-M 21	SILTRON 21 - MASTER ROLL	LINEAR FT	150	675 lbs
SIL-P 28	SILTRON 28 - PRE STAKED	LINEAR FT	50	825 lbs
SIL-M 28	SILTRON 28 - MASTER ROLL	LINEAR FT	150	825 lbs