




LED Wall Pack

Model : SZ-WP80WA (P)


Advantage:

- UL&DLC certificate;
- IP65 Internal driver, with Photocell;
- Input voltage 100-277VAC;
- No UV or IR in the beam;
- Easy to install and operate;
- Energy saving, long lifespan;
- Light is soft and uniform, safe to eyes;
- Instant start, NO humming;
- Green and eco-friendly without mercury.



Application:

Entrance lighting, courtyard lighting;
Industrial lighting, Outdoor landscape lighting;
Building, The hotel;
Wall lighting area and so on.



Specifications

Product name	LED Wall Pack
Part No	SZ-WP80WA
Dimension	360*235*186mm

Technical Characteristic

Color temperature	5000K/5700K
CRI	>80
Lumen	9600LM
Lumen Efficacy	120LM/W
Input Power	80W
Viewing Angle	110 Degree
Input Voltage	100-277VAC 50/60Hz
Driver model	China Brand Driver
Photocell	Yes
PF	>0.9
Waterproof Rating	IP65

Materials



LED Type	3030/1.5W
LED QTY	110PCS
Housing	Aluminum(ADC12) +PC
Housing color	Brown

Others

Operating Temperature	-20℃ TO 45℃
Operating Humidity	20%-90% RH
Storage Temperature	-30℃ TO 80℃
Storage Humidity	10%-95%
Application	Outdoor / Indoor
Safety Certification	UL&DLC
Warranty Time	5 Years

Light Distribution Testing Parameters

DATA OF LAMP		PHOTOMETRIC DATA Eff: 123.92 lm/W			
MODEL		I _{max} (cd)	3724	S/MH (C0/180)	1.17
NOMINAL POWER (W)	80	LOR (%)	100.0	S/MH (C90/270)	0.45
RATED VOLTAGE (V)	120	TOTAL FLUX (lm)	9885.1	η UP, DN (C0-180)	19.6, 69.7
NOMINAL FLUX (lm)	9885.13	CIE CLASS	SEMI-D.	η UP, DN (C180-360)	0.5, 10.3
LAMPS INSIDE	1	η up (%)	20.1	CIBSE SHR NOM	1.00
TEST VOLTAGE (V)	120.0	η down (%)	79.9	CIBSE SHR MAX	1.15



Package

Lamps Net Weight: 3.3kg / pcs

Model	Size	Qty/ Carton	Weight/ Carton
SZ-WP80WA (P)	390*270*245mm	1	3.0 KG



Notice For User

Please turn off power before install or change assembly parts.

The input voltage and lamps should be matched, after connecting the power line, Please make sure the wiring section is insulated.

No-professionals, must not install and disassemble the lamps.

Trouble Shootings

Troubles	Check points
Flickering of the light	Turn off the power and turn on again in 3 minutes. If same phenomena occur, then call agencies
Out of working	Please check the connection