



Product Description

EZ Polish System® Super Sealer PLUS repels both oil and water on most hard surface substrates, providing real stain protection without forming a typical film like “guard” stain protection.

Super Sealer PLUS’ extremely small molecular size allows it to penetrate into dense, hard and non-porous surfaces creating a sub-surface barrier resistant to staining from many foods and chemicals.

Application Directions

Preferred method of application is with a Patriot® pump sprayer fitted with Patriot Green #4 or similar conical mist tip with 4.2 gal/hr flow at 40psi, (15.9 L/hr at 275.8 kPa) and an micro fiber pad. Ambient temperature should be 40-90°F (4- 32°C) during application.



Do not apply over 90°F (32°C); avoid application on hot, windy days. Super Sealer PLUS provides the best protection when applied in a light “film” coat.

1. Spray a light mist of Super Sealer PLUS onto concrete surface and immediately spread evenly with Microfiber pad. Apply enough material to keep the surface wet for about a minute before penetrating; attain 100% coverage, without either dry streaking or puddling.

2. Burnish with a high speed burnisher, fitted with a 3000 grit or finer diamond-impregnated pad or auto-scrub with white pad to remove surface haze.

Floor is ready for light foot traffic when Super Sealer Plus is dry to touch; protect treated surfaces from traffic for at least one hour. Super Sealer Plus gains its chemical resistance and water repellency after 24 hours, and it cures fully within seven days. However, even after becoming densified and polished concrete is still a porous substrate.





Maintenance

Spills of staining agents or acidic etching agents including acidic food substances (e.g. vinegar, pickle juice) should be cleaned up immediately to minimize damage to surface.

Remove dust and debris with a Micro Fiber or dry mop. Surface should be cleaned regularly using an automatic floor scrubber with EZ Cleaner mixed with water according to manufacturer's directions. DO NOT use acidic cleansers.

Super Sealer Plus may be easily re-applied whenever deemed necessary. Reapplication at least once every two years is recommended, but more may be required depending on wear and usage conditions. If an improper cleaner is used, reapplication might be warranted. Clean floor thoroughly, allow to dry completely and then repeat original application instructions.

Storage

Keep containers upright and tightly sealed. Do not allow product to freeze, nor use if it has been frozen. Keep under 110° F.

Coverage

PRODUCT	SHIPPING WT.	CONTAINERS	VOLUME	COVERAGE
Super Sealer PLUS-1	10 lbs.	RTU -1 Gal	1 GAL	3000 Min - 5000 Max

DEGREE OF HAZARD

4 = EXTREME

3 = HIGH

2 = MODERATE

1 = SLIGHT

0 = INSIGNIFICANT

