



Product Description

EZ Polish System® EZ Sealer Wet-Look Finish to beautify, protect and preserve the natural beauty of all your concrete & masonry surfaces. This high-gloss formula can also be used on pavers and artificial stone, and it also makes a great topcoat over stains.

Application Directions

DO NOT THIN. Stir or shake before applying. Use product when Temperature is between 50 - 80 F(10 - 27 C). Do not apply in direct sunlight. Do not apply to wet surfaces or if rain or heavy dew is expected withing 24 hours.

Apply a thin coat using a nylon/polyester brush, 1/4" - 3/8" nap roller, high quality pad applicator or a high quality pump sprayer with an adjustable tip at a spread rate of 200-450 sq ft (19-42 m2) per gallon. Spread rate is highly dependent on surface roughness and porosity. If sprayed, backroll to uniform thickness with a microfiber pad.

Allow First coat to dry 4 hours, then apply a second coat at a spread rate of 350-700 sq. ft (33-65 m2) per gallon. Additional coats (no more than 4) may be added for a higher gloss and added protection.

Uses

EZ Polish System® EZ Sealer Wet-Look Finish can be used on previously coated or Uncoated, Vertical or Horizontal, Interior or Exterior surfaces such as: Pavers, Concrete, Mexican Tile and Unglazed tiles, Brick, Aggregate, Natural and Artificial stone, and Masonry.

Not recommended for use on Wood, Metal, Granite, Marble, Terrazzo, areas imediately adjacent to pools or areas subject to hydrostatic pressure. Do not use over Oil-Based products.

Clean Up

- Use Soap and Water.
- Properly dispose of all soiled rags and protect unused product from freezing
- For disposal of empty containers and unused paint, contact your household refuse collection service



P.O. Box 710931 - Santee, CA 92072
(844)3POLISH - EZPolishSystem.com





Features/Benefits

- High Gloss Clear Finish
- Excellent Topcoat Over Paints & Stains
- 100% Acrylic for Maximum Durability
- Interior/Exterior & Vertical/Horizontal
- Resists Hot Tire Pick Up
- Non-Yellowing

Dry Time


- Dries to touch in 1 hour. Longer dry time required in cooler temperatures and in higher humidity
- Floors may be subjected to light foot traffic after 24 hours. Allow 72 hours before repositioning furniture or subjecting surface to heavy foot or automotive traffic.
- Park tires on corrugated cardboard for 14 days after applying product.
- Wait at least 28 days before cleaning with a mild, non-abrasive liquid detergent.

Coverage

PRODUCT	SHIPPING WT.	VOLUME	COVERAGE
Seal Wet-Look Finish-5	50 lbs.	5 GAL	200ft Min - 450ft Max

DEGREE OF HAZARD

- 4 = EXTREME
- 3 = HIGH
- 2 = MODERATE
- 1 = SLIGHT
- 0 = INSIGNIFICANT



Packaging

- 5 Gallon (18.9 L) Pails
- 55 Gallon (208.2 L) Drums
- 275 Gallon (1041 L) Totes



**P.O. Box 710931 - Santee, CA 92072
(844)3POLISH - EZPolishSystem.com**