

APOLLO XL

160mm Downlight

LEVEL 2
STD

Apollo XL is designed to retrofit larger downlight units. With the combination of available accessories it can cover 190mm requirements with an adapter plate or 160mm on its own, making it extremely versatile and an economic option when compared to large commercial fittings.

General Specifications

Delivered Lumens ²	1000lm @ 3000K
Classification	IC-F
Driver	Phoenix Series Insulation Coverable
IP Rating ⁴	IP65
Power	11W (System)
Warranty ¹	7-Years
Beam Angle	120°
Colour Rendering	~83CRI (Typical)
Dimmable ³	Yes - Leading + Trailing
CCT Options	3000K
Colour/s	White
Material	Aluminum Powder Coated
Clearances	SCB = 0 HCB = 0
Size	Cutout: 122-152mm Depth: 38.8mm Trim: 160mm

80+
CRI11
WATT1000
LM

IC-F

LOW
PROFILE

120°

Key Facts



The King of Retrofit

Highly versatile trim design for a wide range of larger retrofits



Low Profile Design

Fits under building elements and fully insulation coverable.



Long Life by Design

Boasting a 50,000hr L70 rated lifespan for long term ownership.



Assembled in Christchurch

Supporting extremely high quality standards and a local workforce.

Accessories



190mm Expansion



XL Spring Clip

Product Options

SKU Example: A160-DW3K (Dimmable / White Trim / 3000K)

SKU	Driver	Trim	CCT	Optics	Technology
A160	(D) Dimmable	(W) White	(3K) 3000K	(_)120° Optic	N/A

(1.) Warranty for residential use. 5 Year warranty for commercial use. (2.) Subject to a +-5% light production tolerance. (3.) Processor ability. Not applicable to all dimmer mechanisms. Specifications are provided on an 'as is' basis and are subject to change without notice. (4) Refers to the front of the lamp. Rear of lamp is IP40.