



Color Box



WASHDOWN PUMP KIT

FEATURES & BENEFITS

- Positive displacement pump
- Can run dry
- Quiet operation
- Demand pump
- Easy connect fittings
- Ignition protected
- Industry standard mount pattern

PUMP

- Liquid temperature**
140 °F (60 °C) Max.
- Priming Capabilities**
6 feet (1.8 m) suction lift
- Inlet/Outlet Ports**
1/2" -14MNPT
- Weight**
8.2 lbs (3.72 kg) -51 series

INCLUDES:

- (1) 3.0/5.0 GPM Heavy-Duty Washdown Pump
- (2) Trigger Spray Nozzle w/ Quick Connect
- (3) 25' Coiled Hose (UV Protected, 1/2")
- (4) Quick Hose Disconnect Fitting
- (5) 50 Mesh Inlet Strainer
- (6) 1/2" Barbed Fittings



More details and other optional accessories
 please refer to page 87-88



Blister

STANDARD PUMP CONFIGURATIONS

Model	Voltage	Switch	GPM/LPM	PSI/BAR	Max Draw(A)	Valves	Diaphragm	Ports	Wire Connections
SFWP1-040-070-51	12 V	Demand	5.0/18.9	70/4.8	18	EPDM	Santoprene	1/2"-14 MPNT	2-Pin/Leads
SFWP2-050-070-51	24 V	Demand	5.0/18.9	70/4.8	9	EPDM	Santoprene	1/2" -14 MPNT	2-Pin/Leads