

F3CL076

CANTILEVER TAIL-LIFT

LOAD CAPACITY: 750 KG



DESCRIPTION

The 3 cylinders F3CL O76 is a very light strong and compact lift, with very high performances. Smooth hydraulic automatic tilt. High stiffness ideal to equip vehicles for customers that like high performances. The F3CL O76 is available with a wide variety of quick-fit mounting plates, to suit most commercial vehicles and light trucks up to 6.5T GVW. Main beam: tailor made to suit most commercial vehicles such as:

- Fiat DUCATO Citroen JUMPER Peugeot BOXER
- Ford TRANSIT
- Iveco DAILY
- Mercedes Benz SPRINTER
- Renault MASTER Opel MOVANO
- Volkswagen CRAFTER Man TGE

SPECIFICATIONS

Platform:	Aluminium
Platform depth:	from 1600 to 2000 mm rear bumper EEC type approved
Lift cyliders:	1
Tilt cylinders:	2
Autotilt at ground:	hydraulic (with memory feature)
Platform opening:	Gravity opening
Power supply:	12 or 24 V
Low maint. bushes:	greasable
Frame color:	Black KTL plus and powder paint
Weight:	from 178 Kg

SUGGESTED OPTIONS

- Inside body remote control;
- Radio remote control;
- Foot operated controls on platform;
- Blinking lights on platform;
- Roll stop;
- Platform lock handle;
- Body seal kit;













F3CL076

CANTILEVER TAIL-LIFT

LOAD CAPACITY: 750 KG

TECHNICAL DATA

Mod.	Arm width	Load Capacity (600 mm load centre)	Standard platform dimension		Weight*	Floor to ground	Floor to bottom of chassis		Mounting space
			Depth	Width	(Kg)	(max)	min	max	min
F3CL 076 C	W44 (440 mm)	750 Kg	1200 1400 1600	on demand	205 225 245	980	240	420	441
F3CL 076 C1						1100	280	480	485
F3CL 076 H			1800		285	1200	300	530	550

^{*}Approximate weight for tail-lift equipped with aluminium platform dimensions 1400 x 2200 mm.

The above mentioned weights are approximate and may vary according to production. Anteo reserves the right to change weights and technical specifications without prior notice. No indemnity for damages can be claimed from Anteo for changes in technical specifications and/or in weight.

ALUMINUM REAR BUMPER BAR up to 3,5T GVW

STEEL REAR BUMPER BAR up to 6,5T GVW







LOW MAINTENANCE BUSHES AND CHROMIUM PLATED PINS.



POWDER COATING PAINT (2) ADDED TO KTL PLUS (1). NO RUST AND NO SALT STAINS.



HI-TENSILE ALUMINUM SPECIALISTS SINCE 1992.



LOW NOISE POWER UNIT & NO ELECTRONICS = EASY MAINENANCE







