

■ Notice

- ⚠ Do not plug in together with other several plugs at once.
The fire can be caused from overheating.
- ⚠ Do not bend a plug before, and do not put any heavy article on a plug.
It can cause the fault of operation owing to inferior power, and the fire can be caused from short circuit.
- ⚠ Do not touch a plug with wet hand.
It can cause electric shock.
- ⚠ Plug in certainly to prevent a plug from being shaken.
If the connection is not completed, the fire can be caused from overheating.
- ⚠ Do not assemble or remodel the main body of electric signboard.
It can cause the danger of fire, electric shock, and injury owing to wrong operation.
- ⚠ If there is smoke or strange smell from the product, stop using this product immediately, power off, plug out, and then call to service center. It can cause the fire.
- ⚠ Do not give any shock to product or drop this during the carriage.
It can cause the defect.
- ⚠ Fix the product firmly not to be dropped.
If the product falls off, it can cause defect and damage.
- ⚠ Keep this product away from vibration or magnet.
It can cause the defect.
- ⚠ Do not disassemble a remote control.
It can cause the defect.

CONTENTS


- Before Use
 - ◆ Features of Product ----- 4
 - ◆ Name and Function of Remote Control Buttons ----- 5
 - ◆ How to input characters with remote control ----- 6
- Basic Directions for Use
 - ◆ Basic method of inputting advertisement on electric signboard ----- 7
- How to use Menu Function
 - ◆ Menu List ----- 8
 - 1. AD.APPEND ----- 9
 - ① Add.Text
 - ② Add.Image
 - ③ Add.Movie
 - ④ Add.Anima
 - ⑤ Add.Date
 - ⑥ Add.Time
 - ⑦ Add.D-Day
 - 2. AD.RESERVE ----- 12
 - 3. AD.MODIFY ----- 12
 - 4. AD. List ----- 13
 - 5. AD.INSERT ----- 13
 - ① DEL.ONE
 - ② DEL.ALL
 - 7 ST.TIME ----- 14
 - ① ST.DATE
 - ② ST.TIME
 - ③ ON TIME
 - ④ OFF TIME
 - 8 ST.PRODUCT ----- 16
- Kind of Effect
 - ◆ START EFFECT ----- 18
 - ◆ WAIT EFFECT ----- 18
 - ◆ END EFFECT ----- 19
- Appendix 1, 2, 3
 - ◆ Repair & Inspection ----- 20
 - ◆ Management Menu ----- 23
 - ◆ Special character input(Symbol, ICON, Language) ----- 24

■ Before Use

◆ Features of Product

- ▶ Free adjustment of SIZE
1 column 6 lines basis, Module can be reduced and expanded by request of customers.
- ▶ More than 4 times Brighter
Brightness is increased by adopting 1/8 Duty Way
- ▶ 100% water-proof (Outdoor)
Full water-proof using special silicon coating of U.S Dowcorning
- ▶ Development of our own Korean-input Remote control
It is possible to input Korean characters easily with our own Korean-input way, and also to use accurately owing to beep made when pushing the button of remote control.
- ▶ Auto Electric Signboard ON/OFF
Turn On/Off electric signal board by setting service time with Start/End/Reserve function
- ▶ Display of Date/Time
Various graphic effects of TIME/DATE can be displayed with Watch Chip built in electric signalboard, and Event Period can be displayed more effectively by adding D-Day as well.
- ▶ 6 kinds of font available
Unlike previous product applying 2~3 kinds of font, this product can realize various expression with 6 fonts.
- ▶ Each character can express 20 separate effects
- ▶ Special effects more than 100 kinds
It is possible to realize various expression that cannot be realized with previous product.
- ▶ Thin and light external frame
Thin and beautiful frame adopting aluminum frame
- ▶ Convenient adjustment of remote control
It is possible to conveniently **adjsut** remote control by adopting the same way as mobile phone.
- ▶ Simple installation
- ▶ Reliable and fast A/S
We provide exchange service and A/S for any defective product during the warranty period, and any maintenance is not necessary after installation.

■ Name and Function of Remote Control Buttons



Power button is used to Power On/OFF

Menu button is used to activate the control function of electric sig

COL button is used to change color of character

Width button is used to adjust the size of character.

EFF button is used to give effect to character

Font button is used to change font

KOR button is used to input Korean characters

ENG button is used to input English capitals

eng button is used to input English small letters

NUM button is used to input numbers

Delete button is used to delete previous character

Space button is used to add blank

Effect button is used to select various kinds of effect or menu

Speed button is used to adjust the speed of each effect

OK button is used to select function

Light button is used to give light effect

ESC button is used to cancel the input of function and character

Copy button is used to give color or effect to previous character

DEMO button is used to demo several effects

Neon button is used to add neon effect

Fix button is used to fix character in the center

SPE button is used to input special characters

Move button is used to insert animation

Icon button is used to input stop icon

SYM button is used to input symbols

あ button is used to input Japanese Hirakana

ア button is used to input Japanese Katakana

CHI button is used to input Chinese characters

LANG button is used to input the third foreign language

■ Before Use 2

◆ How to input characters with remote control

- ▶ When inputting "啊"
- ▶ When inputting "标"
- ▶ When inputting "黑"
- ▶ When inputting Symbol Characters
- ▶ When inputting Special Characters and Icon
- ▶ When inputting Animation
- ▶ When giving font, color, outline, and effect to characters, move a cursor to relevant character with the key 'Left/Right', and then modify it with the key "Color", "Width", "Effect", and "Font".

◆ How to input basic advertisement in electric signalboard

- ▶ Push the button "Menu" on remote control
 - ▶ When the menu "1:ADD.APPEND" is on screen, push the button "OK".
 - ▶ When the menu "①Add.Text" is on screen, push the button "OK".
 - ▶ When the message "ADD.TEXT" is displayed and then disappeared, add desirable advertisement text.
 - ▶ When text is added, push the button "OK". Then "SEL.START EFFECT" is displayed and disappeared.
 - ▶ When the message "ⓄEff.Auto" is on screen, push the button "Up/Down" to select Start Effect, and then push the button "OK" to preview designated effect. In the state of preview, push the button "Up/Down" to modify the direction or type of effect, and push the button "Left/Right" to modify the speed of effect. After deciding desirable setting, push the button "OK" to save START EFFECT.
 - ▶ When START EFFECT is set, the message "SEL.WAIT EFFECT" is displayed and then disappeared. Select the maintenance effect with the button "Up/Down" to preview. In the state of preview, push the button "Up/Down" to modify the direction or type of effect, and push the button "Left/Right" to modify the speed of effect. After deciding desirable setting, push "OK" to save WAIT EFFECT.
 - ▶ When WAIT EFFECT is set, the message "WAIT TIME[03]" is on screen. Set WAIT TIME, and push the button "OK" to save WAIT TIME.
 - ▶ When the message "SEL.END EFFECT" is displayed and then disappeared, select effect with the button "Left/Right". Decide END EFFECT, and then push the button "OK" to preview. In the state of preview, push the button "Up/Down" to modify the direction or type of effect, and the button "Left/Right" to modify the speed of effect. After deciding desirable setting, push the button "OK", then the message "COMPLETE" is displayed and then disappeared, and all advertisement effects are saved.
- When the message "1:AD.APPEDN" is on screen, push the button "CANCEL" to display advertisement text on electric signalboard.

■ How to use menu function

◆ Menu List

1: AD.APPEND

- ①ADD.TEXT ②ADD.IMAGE ③ADD.MOVIE ④ADD.ANIMA
⑤ADD.DATE ⑥ADD.TIME ⑦ADD.D-DAY

2: AD.RESERVE

3: AD.MODIFY

4: AD.LIST

5: AD.INSERT

6: AD.DELETE

- ①DEL.ONE ②DEL.ALL

7:ST.TIME

- ①ST.DATE ②ST.TIME
③ON TIME ④OFF TIME

8:ST.PROD

- ①POWER(X)
②BEEP(O)
③DIRECTION(HORIZONTAL)
④PASSWORD(X)
⑤BRIGHTNESS

1. AD.APPEND

①ADD.TEXT

- ▶ Push the button "Menu" on remote control.
- ▶ When the message "1:AD.APPEND" is on screen, push the button "OK".
- ▶ When the message "①ADD.TEXT" is on screen, push the button "OK".
- ▶ When the message "ADD.TEXT" is displayed and then disappeared, cursor flickers on the left side
- ▶ After adding desirable advertisement, move a cursor to relevant character with the button "Left/Right" and then push the button "Color", "Width", "Effect", and "Font" to embody various fonts and attributes.
- ▶ When advertisement text is input, push the button "OK", the message "SEL.START EFFECT" is displayed and disappeared.
 - ※ What is START EFFECT? The effect when the advertisement text is initially displayed.
- ▶ The message "①Eff.Auto" is on screen. Push the button "Up/Down", and then the menu '02:Eff.03:Eff.View 04:Eff.Scroll 05:Eff.Wave 06:Eff.Zoom 07:Eff.Color 08:Eff.Twist 09:Eff.None' is displayed on screen, and user can select one menu with the button "OK".
- ▶ Select desirable START EFFECT with the button "OK" to preview designated effect.
In the state of preview, push the button "Up/Down" to modify the direction or type of effect, and push the button "Left/Right" to modify the speed of effect.
Push the button "OK" again to save START EFFECT after deciding desirable effect(Push the button "CANCEL" to go back to previous menu after selecting effect).

※ On the basis of 1 column 6 lines, when advertisement text exceeds 6 characters, it will be displayed with being scrolled to the left after the setting is displayed.
In the state of preview, push the button "NEON" to input "Neon Effect" when adding text, and NEON EFFECT is expressed. Push the button "Up/Down" continuously, and NEON effect is expressed in various forms.

■ HOW TO USE MENU FUNCTION 2

- ▶ When START EFFECT is set, the message "**SEL. WAIT EFFECT**" is displayed, and then disappeared.

※ What is WAIT EFFECT? The effect is displayed for the fixed time at a standstill while advertisement is being fixed on screen after START EFFECT is finished.

- ▶ After the message "**SEL. WAIT EFFECT**" is disappeared, the message "**⓪Eff.Auto**" is on screen. Push the button "Up/Down" to select "**⓪Eff.Auto** **⓪Eff.Anim** **⓪Eff.View** **⓪Eff.Wave** **⓪Eff.Zoom** **⓪Eff.Color** **⓪Eff.Twist** **⓪Eff.None**".
- ▶ Select WAIT EFFECT to preview. In the state of preview, push the button "**Up/Down**" to modify the direction or type of effect, and push the button "**Left/Right**" to modify the speed of effect. After deciding desirable effect, push the button "**OK**" again to save WAIT EFFECT.
- ▶ When WAIT EFFECT is set, the message "WAIT TIME[03]" is on screen. WAIT TIME can be set in seconds from 01 to 99, and [03] means 3 seconds. Set WAIT TIME, and push the button "**OK**" to save WAIT TIME.
- ▶ When the message "**SEL.END EFFECT**" is displayed and then disappeared, the message "**⓪Eff.Auto**" is on screen. Push the button "Up/Down" to select "**⓪Eff.Auto** **⓪Eff.Anim** **⓪Eff.View** **⓪Eff.Scroll** **⓪Eff.wave** **⓪Eff.Zoom** **⓪Eff.Color** **⓪Eff.Twist** **⓪Eff.None**".
- ▶ Select END EFFECT to preview. In the state of preview, push the button "Up/Down" to modify the direction or type of effect, and push the button "Left/Right" to modify the speed of effect. After deciding desirable effect, push the button "**OK**" again, and the message "COMPLETE" is displayed and then disappeared, adding text is completed, and the message "**⓪AD.APPEND**" is on screen again. Repeat the process above to add text continuously, and push the button "**CANCEL**" or "**MENU**" to complete.

⓪ADD-ENG-2L

⓪ADD.IMAGE

- ▶ Push the button "**Menu**" on remote control.
- ▶ When the message "1:AD.APPEND" is on screen, push the button "**OK**".
- ▶ When the message "2:Add.Image", push the button "**OK**".
- ▶ Input in the same way as "**⓪ADD.TEXT**".

⓪MOVIE, ⓪ANIMATION

- ▶ Push the button "**Menu**" on remote control.
- ▶ When the message "1:AD.APPEND" is on screen, push the button "**OK**".
- ▶ When the message "3:MOVIE" is on screen, push the button "**OK**".
- ▶ Input in the same way as "**⓪ADD.TEXT**".

⓪ADD.DATE

- ▶ Push the button "**Menu**" on remote control.
- ▶ When the message "1:AD.APPEND" is on screen, push the button "**OK**".
- ▶ When the message "5:Add.Date" is on screen, push the button "**OK**".
- ▶ Input in the same way as "**⓪ADD.TEXT**".

⓪ADD.TIME

- ▶ Push the button "**Menu**" on remote control.
- ▶ When the message "1:AD.APPEND" is on screen, push the button "**OK**".
- ▶ When the message "6:Add.Time" is on screen, push the button "**OK**".
- ▶ Input in the same way as "**⓪ADD.TEXT**".

⓪D-DAY ⓪D-TIME

- ▶ **⓪ADD.DATE** and **⓪ADD.TIME** should be implemented before **ADD.D-Day**.
- ▶ Push the button "**Menu**" on remote control.
- ▶ When the message "1:AD.APPEND" is on screen, push the button "**OK**".
- ▶ When the message "7:Add.D-Day" is on screen, push the button "**OK**".

⓪ADD-TEMP

■ HOW TO USE MENU FUNCTION 3

- ▶ When the message "09/03/03" is on screen, move a cursor to Y/M/D with the button "Left/Right", and then set Y/M/D with the button "Up/Down".
Push the button "OK" after setting, and the message "Complete" is displayed for a little while, and then disappeared, then the message "ADD.D-DAY" is displayed. When a cursor flickers on the right side, and D-0 is on screen, input D-DAY, and push the button "OK" to save D-DAY.
- ▶ The color effect of "D-0" can be modified with the button 'Light'.

2. AD.RESERVE

This function is to express added text at the designated time.

- ※ The saved reservation is expressed at the designated time everyday.
- ※ The expression of saved reservation can be set in MAIN MENU "AD.LIST".

@RSV.Event

- ▶ Push the button "Menu" on remote control.
- ▶ When the message "1:AD.APPEND" is on screen, select AD.RESERVE with the button "Up/Down", and then push the button "OK". Then when the message "@RSV.Event" is on screen, push the button "OK", and then when the message "ADD.TEXT" is on screen, push the button "OK" after adding text, and input in the same way as "ADD.TEXT".

@RSV.Time

- ▶ Push the button "Menu" on remote control.
- ▶ When the message "1:AD.APPEND" is on screen, select AD.RESERVE with the button "Up/Down", and then push the button "OK". Then when the message "@RSV.Event" is on screen, push the button "OK".
- ▶ Push the button "OK" after selecting desirable event from Event List inserted "@RSV.Event", and then input On Time and Off Time of Event in order.

3. AD.MODIFY

This function is to modify the previously saved TEXT/DATE/TIME/D-DAY/EVENT.

- ▶ Push the button "Menu" on remote control.
- ▶ When the message "1:AD.APPEND" is on screen, select "3:AD.MODIFY" with the button "Up/Down", and then push the button "OK".
- ▶ Previously saved TEXT/DATE/TIME/D-DAY/EVENT are displayed in the form of "01:CONTENT".

- ▶ Select desirable text to modify with the button "Up/Down", and then push the button "OK".
- ▶ After modifying advertisement, push the button "OK" to set START EFFECT/WAIT EFFECT/END EFFECT again in the same way as "AD.APPEND".

4. AD.LIST

This function is to select the expression of the saved advertisement such as TEXT/DATE/TIME/D-DAY/EVENT. O: ON / X: OFF

- ▶ Push the button "Menu" on remote control.
- ▶ When the message "1:AD.APPEND" is on screen, select "3:AD.MODIFY" with the button "Up/Down", and then push the button "OK".
- ▶ Previously saved TEXT/DATE/TIME/D-DAY/EVENT are displayed in the form of "01:CONTENT".
- ▶ Select desirable text to modify with the button "Up/Down", and then push the button "OK".
- ▶ Push the button "Left/Right" to express the selected advertisement.

5. AD.INSERT

This function is to add new advertisement between the previously saved TEXT/DATE/TIME/ D-DAY/EVENT.

- ▶ Push the button "Menu" on remote control.
- ▶ When the message "1:AD.APPEND" is on screen, select "4:AD.INSERT" with the button "Up/Down", and then push the button "OK".
- ▶ Previously saved TEXT/DATE/TIME/D-DAY/EVENT are displayed in the form of "01:CONTENT".
- ▶ Push the button "Up/Down" to decide the desirable position of advertisement, and then push the button "OK".
 - ※ For example, push the button "OK" in No.2 to insert new TEXT between advertisement No.1 and No.2.
- ▶ Then input in the same way as "ADD.TEXT".

■ HOW TO USE MENU FUNCTION 4

6. AD.DELETE

This function is to delete the previously saved TEXT/DATE/TIME/D-DAY/EVENT partially or entirely. * **Caution: Deleted advertisement cannot be restored.**
Please, check before deleting advertisement.

⓪DELETE ONE

- ▶ Push the button "**Menu**" on remote control.
- ▶ When the message "**1:AD.APPEND**" is on screen, select "**5:AD.DELETE**" with the button "**Up/Down**", and then push the button "**OK**".
- ▶ When the message "①DEL.ONE" is on screen, push the button "**OK**" immediately, and the message "01:CONTENT" is on screen.
- ▶ Push the button "**Up/Down**" to decide the position of desirable advertisement to delete, and then push the button "**OK**" to delete the relevant advertisement.

ⓐDEL.ALL

⚠ **Caution: All the saved advertisements are deleted.**

- ▶ Push the button "**Menu**" on remote control.
- ▶ When the message "**1:AD.APPEND**" is on screen, select "**5:AD.DELETE**" with the button "**Up/Down**", and then push the button "**OK**".
- ▶ When the message "①Del.One" is on screen, push the button "**Up/Down**" to select "②Del.All", then push the button "**OK**" immediately, and the message "DELETE?(Y/N)" is on screen. Then push the button "**OK**" to delete all the advertisements, and the message "COMPLETE" is on screen.

7. ST.TIME

This function is to display DATE/TIME, and set ON TIME/OFF TIME.

⓪ST.DATE

- ▶ Push the button "**Menu**" on remote control.
- ▶ When the message "**1:AD.APPEND**" is on screen, select "**6:ST.TIME**" with the button "**Up/Down**", and then push the button "**OK**".
- ▶ When the message "①ST.DATE" is on screen, push the button "**OK**", and present date is displayed.
- ▶ When the present date, for example "09/03/03", is on screen, move a cursor to Y/M/D with the button "**Left/Right**", and then push the button "**Up/Down**" to set desirable date to modify.
- ▶ After setting date, push the button "**OK**" to save new date, and the message "COMPLETE" is on screen.

ⓐST.TIME

- ▶ Push the button "**Menu**" on remote control.
- ▶ When the message "**1:AD.APPEND**" is on screen, select "**6:ST.TIME**" with the button "**Up/Down**", and then push the button "**OK**".
- ▶ When the message "①ST.DATE" is on screen, push the button "**Up/Down**" to select "②ST.TIME", push the button "**OK**", and the present time is on screen, for example "10:01:10".
- ▶ Move a cursor to HOUR/MINUTE/SECOND with the button "**Left/Right**", and then push the button "**Up/Down**" to set desirable time.
- ▶ After setting time, push the button "**OK**" to save new date, and the message "COMPLETE" is on screen.

ⓑON TIME/ⒸOFF TIME

- ▶ Push the button "**Menu**" on remote control.
- ▶ When the message "**1:AD.APPEND**" is on screen, select "**6:ST.TIME**" with the button "**Up/Down**", and then push the button "**OK**".
- ▶ When the message "①ST.DATE" is on screen, push the button "**Up/Down**" to select "③ON TIME/④OFF TIME", and then push the button "**OK**".
- ▶ When the present time is on screen, move a cursor to AM/PM, HOUR, MINUTE with the button "**Left/Right**", and then push the button "**Up/Down**" to set desirable time.
- ▶ After setting time, push the button "**OK**" to set ON TIME/OFF TIME, and the message "COMPLETE" is on screen.
- ▶ With this function, it is possible to turn electric signal ON/OFF for desirable time.

■ HOW TO USE MENU FUNCTION 5

7. ST.PRODUCT

This function is used to turn ON/OFF power, beep, direction, password, brightness, etc.

- ▶ Push the button "Menu" on remote control.
- ▶ When the message "1:AD.APPEND" is on screen, select "7:ST.PROD" with the button "Up/Down", then push the button "OK", and the message "①ResvX" is on screen.
- ▶ Push the button "Up/Down" to select ①POWER ②BEEP ③DIRECTION ④PASSWORD ⑤BRIGHTNESS, then push the button "OK", and the relevant function is changed to O/X.
(O: On, X: Off)
- ▶ When option setting is completed, push the button "CANCEL".

①ST.POWER means the operation condition after setting ON TIME/OFF TIME.

(O: On, X: Off)

②BEEP means the sound made when pushing the button of remote control.

(O: On, X: Off)

③DIRECTION is the function to change the direction of electric signalboard.

(Horizontal, Vertical)

④PASSWORD is to prevent advertisement from being modified by other person at random.

(O: On, X: Off)

⑤BRIGHTNESS is to modify the brightness of electric signalboard to DAY/NIGHT mode.(Level 1~10)

■ KIND OF EFFECT

◆ KIND OF START EFFECT

- ① **Eff.Auto** Display effect automatically without any appointment
- ② **Eff.Anim** Various animation effects
- ③ **Eff.View** Display characters directly on screen in several types
- ④ **Eff.Scroll** Scroll in order of left/right/up/down
- ⑤ **Eff.Wave** Wave left/right/up/down
- ⑥ **Eff.Zoom** Zoom characters in several directions
- ⑦ **Eff.Color** Separate/Mix characters according to color
- ⑧ **Eff.Twist** Display characters in twisted shape
- ⑨ **Eff.None** Display without any effect

◆ KIND OF WAIT EFFECT

- ① **Eff.Auto** Display effect automatically without any appointment
- ② **Eff.Anim** Various animation effects
- ③ **Eff.View** Display characters directly on screen in several types
- ④ **Eff.Wave** Wave left/right/up/down
- ⑤ **Eff.Zoom** Zoom characters in several directions
- ⑥ **Eff.Color** Separate/Mix characters according to color
- ⑦ **Eff.Twist** Display characters in twisted shape
- ⑧ **Eff.None** Display without any effect


◆ KIND OF END EFFECT

- ① **Eff.Auto** Display effect automatically without any appointment
- ② **Eff.Anim** Various animation effects
- ③ **Eff.View** Display characters directly on screen in several types
- ④ **Eff.Scroll** Scroll in order of left/right/up/down
- ⑤ **Eff.Wave** Wave left/right/up/down
- ⑥ **Eff.Zoom** Zoom characters in several directions
- ⑦ **Eff.Color** Separate/Mix characters according to color
- ⑧ **Eff.Twist** Display characters in twisted shape
- ⑨ **Eff.None** Display without any effect

■ APPENDIX(1)

◆ REPAIR & INSPECTION

1. When Power of electric signal board cannot be ON
 - 1) check if the plug is in an outlet.
 - 2) Please, plug out from an outlet, and then plug in again 10 seconds later.
 - ※ If it does not work after following procedure above 3 times, please request A/S.
2. When a remote control is not working
 - 1) Use a remote control in accurate position, because the responder is in the middle on the right side of electric signalboard.



- 2) Check if the battery is in remote control, and it is used for too long time.
- 3) If there is any defect, please request A/S.

◆ Standard and Option of Product

PRODUCT NAME	LED Signboard(Remote Control Type)
ENVIRONMENT	Indoor/Outdoor
LUMINOUS COLOR	Single color(Red, Yellow) 3-Color(Red/Green/Yellow, Blue), Full color
EXTERNAL COLOR OF PRODUCT	Black Silver
COMMUNICATION	Infrared remote control/ PC(option)
RATED INPUT VOLTAGE	AC85-250V(single color) / AC220V(3 Color) / 50 / 60Hz, DC12V/ 24V, 2M(for car)
POWER CONSUMPTION	Mean power consumption 20W/ Max. 40W(single color) Mean power consumption 40W/ Max. 80W(3-color)
CAPACITY OF MEMORY	Maximum 100 Texts in Korean(256 characters) and in English(512 characters) can be input
POWER CODE	AC 220V

◆ Management Menu

BASIC LANGUAGE/NUMBER OF COLUMNS/COLOR can be set and tested before delivering the product.

- ※ In the event of modifying settings on some menu, the settings of advertisement product are initialized.
- ※ How to select Management Menu
 - ① If DEMO or ADVERTISEMENT is on replay, push the button "POWER" to POWER OFF.
 - ② When POWER is OFF, push the button "Font" 4 times to enter in TEST MODE.
 - ③ In TEST MODE, push the button "CANCEL" to enter into MANAGEMENT MENU.

① MANUFACTURE

This menu is to modify a manufacturing company.

- ▶ In MANAGEMENT MENU, push the button "Up/Down" to select "[1] MANUFACTURE", and then push the button "OK".
- ▶ It is possible to modify a manufacturing company, and set TEXT EFFECT in the same way as MAIN MENU 'AD.APPEND>ADD.TEXT'.
 - ※ It is possible to set color, width, and font of character, except effect.

② VERSION

This menu is to check the firmware version of controller.

③ PRODUCTION

This menu is to check the date of manufacture of controller.

④ TEST

This menu is to test color and line of LED.

- ※ This menu is basically run when MANAGEMENT MENU is selected.

⑤ COLUMN

This menu is to modify the number of columns.

- ※ Advertisement is expressed with the number of columns, apart from the number of columns of real product. Check the number of columns before modifying.

- ▶ In MANAGEMENT MENU, push the button "Up/Down" to select the menu "[5] COLUMN", and then push the button "Left/Right" to modify the number of columns.

⑥ COLOR

This menu is to set the color that product can express.

- ※ Color expressed by controller is set, apart from color that real product can express. When setting color to single color, advertisement is expressed in single color, even if electric signalboard can express it in more than 3 colors.

- ▶ In MANAGEMENT MENU, push the button "Up/Down" to select the menu "[6] COLOR", and then push the button "Left/Right" to modify color.
 - 1 : Single color(R or G), 3 : 3 Colors(R,G,Y)

⑦ LANGUAGE

This menu is to set basic language of product. When adding MENU and TEXT, basic language is changed according to language setting.

- ※ KOR – Korean Menu, Insert Korean / ENG – English Menu, Insert English / CHN – Chinese Menu, Insert Chinese

- ▶ In MANAGEMENT MENU, push the button "Up/Down" to select the menu "[7] COLOR", and then push the button "Left/Right" to modify language. and then push the button "Left/Right" to modify language.

