



Seamax Viscus 25W-60

Description

Castrol Seamax Viscus 25W-60 is a high viscosity mineral engine oil specifically designed for vessels with older diesel engines.

Application

Castrol Seamax Viscus 25W-60 is suitable for use in all marine diesel engines calling for an oil with API CF-4 performance. In particular, Castrol Seamax Viscus 25W-60 has been specifically designed for use in heavy duty diesel engines with high operating hours and engines experiencing increased oil consumption. In these applications, Castrol Seamax Viscus 25W-60 is able to help reduce oil consumption and maintain oil pressure, even at high operating temperatures.

Castrol Seamax Viscus 25W-60 is also suitable for use in vessels operating in demanding conditions, such as fishing boats.

Features / Benefits

High performance multigrade diesel engine oil
Helps to minimise oil consumption
Helps to maintain oil pressure and power in units with high operating hours
Maintains constant oil pressure, even at high operating temperatures

Approval Status

SAE 25W-60
API CF-4 / SF

Technical Data

Name	Method	Units	Castrol Seamax Viscus 25W-60
Kinematic Viscosity @ 100°C	ASTM D445	mm ² /s	23
Kinematic Viscosity @ 40°C	ASTM D445	mm ² /s	222
Viscosity Index	ASTM D2270	None	124
Pour Point	ASTM D97	°C	-24
Total Base Number, TBN	ASTM D2896	mg KOH/g	7.3

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Packaging and Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Seamax Viscus 25W-60

29 Feb 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrolmarine.com