



# Hylío AG-116 Spec Sheet - Imperial

Flight Parameters	
Total Weight (without batteries)	39 lb
Max Recommended Takeoff Weight	105 lb
Max Thrust	202.2 lb
Max Operating Speed	25 mph
Propulsion System	
Motor KV	100 rpm/V
Foldable Propeller	30x9.0 in
Configuration	Hexacopter - X
Operating Voltage	12s
Battery	1 x 22000 mAh 12S (44.4V) LiPo Battery
	13.4 lb/battery
Aircraft Frame	
Wheelbase	67 in
Material	Carbon Fiber, Aluminum, Plastic
Dimensions	67x59x24 in (arms unfolded, no propellers)
	35x42x24 in (arms folded, no propellers)
Spray System	
Standard Payload	35 lb, 4.5 gallon
Configuration	1 Pumps, 1 Tank, 1 Flowmeter, 4 nozzle pairs mounted under rotors
Nozzle	Nozzle body compatible with any Teejet spray tip
Pump	Diaphragm Pump, 75 PSI
Flow Rate (no nozzle max)	0.1 – 2.1 Gal/min
Flow Rate (with recommended nozzle AMTGST015)	1.0 Gal/min
Spray Width	Up to 25 feet
Flight Control	
Flight Modes	Fully autonomous (no RC), position hold manual (with RC), Fully manual GPS denied (with RC)
Operating Frequencies	902 – 928 MHz, 2.4 GHz
Ground Station Control Software	Hylío Agrosol
Max Transmission Range	~1 mile (5+ unobstructed)