
Alira

outdoor commercial heat pump with active cooling



MODEL

LWP450

TOTAL POWER (kW)

50

Alira Outdoor Commercial

The Alira outdoor commercial air source heat pump is highly efficient, quiet and is available in 1 model with an output of 50kW. Using the air as the source of energy, the Alira utilises advanced technology to provide sustainable heating and hot water. The Alira can be cascaded (up to 4 units) for larger projects and comes complete with the Luxtronik controller, however, using a BMS system there can be an unlimited number of units.








key features


- Low noise levels
- Operates up to 65°C water temperature
- COP of 3.57 based on EN14511 with water at 35°C and ambient air at 7°C
- Energy efficiency A+ (35°C)
- Weather resistant
- Indoor wall mounted controller included
- Chilled water temperatures of up to 7°C are possible in active cooling mode


warranty

2 year warranty*



DIMENSIONS





VIEW SID	E VIE
----------	-------

		MODEL LWP450
Height	mm	2320
Width	mm	1800
Depth	mm	850
Hot water flow	inches	2
Hot water return	inches	2

TECHNICAL DATA

			MODEL		
			LWP450		
	Air 7°C - Water 35°C	kW	47.8		
heating capacity	COP		3.57		
	Air 7°C - Water 45°C	kW	39.56		
	COP		3.42		
	Air 10°C - Water 35°C	kW	33.38		
i.i.	COP		4.68		
eat	Air -7°C - Water 35°C	kW	38.92		
ے	COP	KVV	2.95		
	Air -10°C - Water 65°C	kW	33		
	COP	KVV	2.57		
	651		2.37		
_					
Ċ.	Air 35°C - Water 18°C	kW	r.r.		
<u>Q</u>	EER	KVV	55 2.5		
cooling capacity	Air 35°C - Water 7°C	kW	24.7		
l ii	EER	KVV			
8	EEK		2.56		
٥					
Se	Total building power	kW	50		
j.	Heating circuit (min / max)	°C	20 / 65		
l si	Cooling circuit (min / max)	°C	10 / 35		
limits of use	Heat source heating (min / max)	°C	-22 / 35		
:=	Heat source cooling (min / max)	°C	10 / 40		
ا ح					
punos	Sound pressure level - 1 metre from	dB(A)	63 / 72.4		
S	edge of unit (min / max)				
ō	Total weight	kg	680		
general data	Refrigerant type/capacity	/kg	R410A - 23		
	Electrical supply	V	415		
	Compressor		2		
gel	Operating pressure	bar	6		
	Electric heating element	kW	N/A		
·					

modutherm

Modutherm Limited Unit 4 Genesis Endeavour Drive Basildon, SS14 3WF

modutherm.co.uk
Tel: 0345 521 5666
enquiries@modutherm.co.uk
A member of the Modular Heating Group.