



FLUIDE IID

Automatic Transmission Fluid

PERFORMANCES LEVELS

OEM-approved

- ✓ ZF TE-ML 03D/04D/14A
- ✓ Voith H55.6335.xx
- ✓ MAN 339 Typ V1/Z1
- ✓ Volvo 97341
- ✓ Mercedes-Benz MB-Approval 236.9

Meets the requirements

- ✓ GM Dexron IID
- ✓ Ford Mercon

Suitable for

- ✓ Allison C4

APPLICATIONS

FLUIDE IID is recommended for automatic or semi-automatic transmissions and torque converters of passenger cars, light commercial vehicles and industrial vehicles, when the manufacturer requires an Automatic Transmission Fluid (ATF) GM DEXRON ® IID.

FLUIDE IID is also recommended for hydrostatic transmissions, power steering applications.

FLUIDE IID is also recommended for hydraulic systems when a fluid type GM DEXRON ® IID is required.

CUSTOMER BENEFITS

- Outstanding thermal stability in operation
- Very high viscosity index
- Excellent resistance to oxidation
- Excellent friction properties specific to the requirements of GENERAL MOTORS Hydramatic

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

FLUIDE IID

Update: 07/2017



- Excellent corrosion protection

PHYSICAL AND CHEMICAL CHARACTERISTICS

FLUIDE IID	Unit	Method	Value
Colour	-	ASTM D1500	Red
Density at 15°C	kg/m ³	ASTM D4052	861
Kinematic Viscosity at 40 °C	mm ² /s	ASTM D445	38,25
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	7,502
Brookfield Viscosity at -40°C	cP	ASTM D2983	22700
Viscosity Index	-	ASTM D2270	169
Pour Point	°C	ASTM D97	-45
Flash Point	°C	ASTM D92	194

**The features mentioned above are average values obtained with some variability in production and do not constitute a specification.*

RECOMMENDATIONS FOR USE

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C while avoiding exposure to strong sunlight, extreme cold or high temperature variations.

All packages should be protected from bad weather conditions. Otherwise, the drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed. The information is accessible on request from your local dealer or on the website www.quickfds.com.

This product should not be used for applications other than those for which it is intended.

If disposing of used product, take care to protect the environment and comply with local regulations.

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

FLUIDE IID
Update: 07/2017



This lubricant does not cause adverse health effects when used in the intended application. A safety datasheet, is accessible on request from your local dealer.

