Technical Data Sheet

Health & Safety For health and safety information please refer to the relevant health & safety data sheet on our website. The content of this data sheet is given in good faith but without warranty. www.oils.today

28 September 2016

Product Description: Linelube Agri ChainSaw Oil

Linelube Chain Saw Oil is a specially formulated chainsaw oil manufactured from solvent refined paraffinic base oil treated with carefully selected additives. Antifling additives help the oil remain on the chain at high speeds and heavy loads. EP additives reduce the fatigue and wear on both bar and chain, Anti rust additives protect the chain when not in use.

Benefits:

- Special anti-wear additives provide exceptional protection against metal-to-metal contact for longer chain life
- For long lasting protection against rust and corrosion

Applications:

Use in high speed applications where it's extra tacky properties will reduce that chances of the oil fling off the chain.

Typical Test Data:

ISO Viscosity Grade	32	68	100	150	220
Kinematic Viscosity: @40°C	32	68	100	150	220
Kinematic Viscosity: @100°C	5.3	8.8	11.4	14.8	17.7
Viscosity Index	105	104	98	92	98
Pour Point °C	-20	-20	-20	-18	-18
Flash Point °C	190	210	210	240	290

Health & Safety:

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

In line with our policy of continued improvement, Online Lubricants Ltd reserves the right to change specification and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. A safety data sheet in conformity with the legislation now current in the EC is available from sales@oils.today .