

linelube Airline Oil ISO 22

Product Description

High quality airline oils with naturally high viscosity indexes, intended for the lubrication of pneumatic tools, valves and related equipment. They have a low pour point and special additives to protect against rust, corrosion and water washing. Airline Oils are intended for use in systems where it may be necessary to draw off any separated water.

linelube Airline Oil is formulated to ensure the quick creation of mist for the lubrication of downstream pneumatic equipment it exhibits low foaming tendencies.

Features & Benefits

- Excellent anti-wear properties
- Good oxidation inhibition
- Anti-rust
- Anti-foam
- Readily separates from water

Applications

Airline Oil is recommended for use in air tools of most types including road drills, jack hammers, air speed saws and torque wrenches. It is also recommended for air motors and the lubrication of pneumatic rams and cylinders.

In addition, Airline Oils can be used for general lubrication in industrial applications.

Typical Test Data

ISO	10	22
Specific Gravity @ 15°C	0.845	0.861
Viscosity @ 40°C (cSt)	10	22
Viscosity @ 100°C (cSt)	2.8	4.4
Viscosity Index	95	100
Flash Point (°C)	178	181
Pour Point (°C)	-25	-25

Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website. The contents of this data sheet are given in good faith but without warranty.