

linelube HP Universal Tractor Oil 10W-30

Product Description

linelube HP Universal Tractor Oil 10W-30 is an advanced high-performance universal oil designed for use in the latest agricultural machinery. It is also recommended for a number of other off-highway equipment including construction, demolition and excavation where any of the specifications below and a SAE 10W-30 viscosity grade are called for.

linelube HP Universal Tractor Oil 10W-30 is formulated using highly refined mineral base stocks together with state-of-the-art additives which provide the ultimate protection against wear and corrosion and help eliminate wet brake noise and chatter.

Features & Benefits

- Fully approved by Massey Ferguson
- Exceptional wear protection
- Enhanced anti-squawk properties providing superior wet brake performance
- Improved low temperature stability
- Meets a variety of OEM requirements
- Suitable for a wide range of off highway machinery requirements
- High API diesel specification

Applications

linelube HP Universal Tractor Oil 10W-30 is suitable for use in naturally aspirated and turbocharged diesel and petrol engines, transmissions, hydraulic systems, final drives, wet brakes and oil immersed clutches.

STOU Specifications

- **Massey Ferguson:** CMS M1145
(Fully Approved): M1144 M1139
- **New Holland:** NH 030C
- **John Deere:** J27
- **FNH:** 8200 9201
- **ZF:** TE-ML 03A; TE-ML 06B, 06C; TE-ML 07B, 07D
- **Ford:** M2C159B/C

UTTO Specifications

- **Massey Ferguson** CMS M1145
(Fully Approved): M1143 M1135
- **New Holland:** NH 420A, NH 410B
- **John Deere:** J20C
- **Case New Holland:** MAT 3525
- **ZF:** TE-ML 03A, TE-ML 06B, 06C, TE-ML 07B, 07D
- **Ford:** M2C134D, M2C86B

Gear & Transmission Specifications

- **API:** GL-4
- **Allison:** C4
- **Caterpillar:** TO-2
- **Afnor:** NFE 68603 E

Engine Specifications

- **ACEA:** E3
- **API:** CG-4, CF-4, CE/SF
- **MB:** 227.1, 228.1
- **MAN:** 271
- **Ford:** M2C121B
- **CCMC:** D4
- **Military:** MIL-L-2104D

Typical Test Data

Specific Gravity @ 15.6°C	0.881
Kinematic Viscosity: @ 40°C	62.0
Kinematic Viscosity: @ 100°C	9.7
Viscosity Index	140
Pour Point (°C)	-36
Flash Point (°C)	223
Total Base Number (mg KOH/g)	10.37

Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website. The contents of this data sheet is given in good faith but without warranty.