



A brand of **TOTAL**

SPORTI TXI 5W-40



Lubricant using ELF synthetics technology, intended for all Gasoline and Diesel car engines.

APPLICATIONS

All Gasoline/Diesel engines
Direct injection Diesel

- Recommended for all Gasoline engines (multivalve, turbocharged, with or without catalytic converter) and all Diesel engines – with or without turbocharging – in cars and light vans.

The most severe journeys
All times of year

- Suitable for all journeys (in town, on highways and motorways) and particularly in severe conditions.

“Vigorous” driving

- For all driving styles, particularly “vigorous” and high speeds.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

PERFORMANCES

International specifications

ACEA : A3/B4
API : SL/CF

CUSTOMER BENEFITS

High performance

- Excellent engine protection, particularly against timing system wear.

Lengthens engine life

- Immediate lubrication of engine parts during cold starts, leading to longer engine life.

Extended oil change intervals

- ELF Sporti TXI 5W-40 meets the requirements of the manufacturers as regards extended oil change intervals.

CHARACTERISTICS

| | Method | Units | SAE Grade 5W-40 |
|--------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D1298 | kg/m ³ | 854 |
| Viscosity at 40°C | ASTM D445 | mm ² /s | 87 |
| Viscosity at 100°C | ASTM 445 | mm ² /s | 14,3 |
| Pour point | ASTM D97 | °C | - 36 |
| Flash point | ASTM D92 | °C | 220 |
| B.N. | ASTM D2896 | mgKOH/g | 10 |

The typical characteristics mentioned represent mean values