

## linelube ATF DEXRON II

### Product Description

ATF Dexron II is formulated from highly refined paraffinic base oils with additive package designed to inhibit oxidation and offer load carrying anti-wear protection.

### Features & Benefits

- ATF Dexron II gives high VI, low pour point, good corrosion and foaming resistance and are modified to create the particular dynamic frictional properties required
- Suitable for most automatic transmission units
- Good long-term anti-wear characteristics
- Suitable for most power steering units

### Applications

ATF Dexron II is suitable for use in most automatic transmissions, torque converters, power steering units and hydraulic pumps as a service fill and top up fluid.

### Specifications

- Allison C4
- Caterpillar TO-2
- G.M. Dexron II
- G.M. Dexron IID
- Ford Mercon
- M2C 138CD & ALHD
- M2C 166H, C5 & ATX
- M2C 33G and Borg Warner
- MB: 236.5 & 236.6
- ZF-TE-ML09, ML11, M114

### Typical Test Data

Density KG @ 15 °C	0.888
Flash point (°C)	229
Flash point COC (°C)	180
Pour point (°C)	-42
Viscosity @ 40°C	44.77
Viscosity @ 100°C	7.86
Viscosity Index	147
Density KG @ 15 °C	0.888

### Typical Physical Properties

Viscosity Index	170
Viscosity @ 100°C c/S	7.0
Viscosity @ -23.3°C c/S	2000
Viscosity @ -40°C c/S	22,000

### Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website. The contents of this data sheet is given in good faith but without warranty.