

linelube Engine Oil Synthetic 5W-30 C3

Product Description

linelube 5W-30 Synthetic Engine Oil C3 is a low-SAPS, fully synthetic, multi-grade engine oil. Advanced additive technology utilised in 5W-30 Synthetic Engine Oil C3 ensures optimum performance of engine components, including diesel particulate filters (DPF) where present. 5W-30 Synthetic Engine Oil C3 is formulated to provide long term protection to emission control systems. Protecting these systems helps to maintain optimal emissions cleanliness throughout the life cycle of an engine, increasing environmental friendliness.

Features & Benefits

- Effective environmental protection
- Maintains performance over extended drain intervals
- Increased fuel efficiency
- High standards of engine cleanliness
- Long term anti-wear and oxidation stability
- Excellent high and low temperature performance

Applications

linelube 5W-30 Synthetic Engine Oil C3 is specifically engineered to meet the performance demands and OEM requirements of the BMW LL-04 and MB 229.51 specifications. 5W-30 Synthetic Engine Oil C3 is suited to applications where high standards of emission control are required under all conditions - including those of vigorous, high speed styles of driving.

Specifications

- **ACEA:** C2, C3
- **API:** SN/CF
- **BMW:** LL-04
- **GM:** Dexos 2
- **MB:** 229.51
- **Peugeot/Citroen:** Meets current specifications
- **Porsche:** C30
- **VW:** 502, 505.01

Typical Test Data

Kinematic Viscosity @ 40°C	72.3
Kinematic Viscosity @ 100°C	11.8
Viscosity Index	160
Pour Point (°C)	-45
Flash Point (°C)	212
Sulphated Ash (% wt.)	0.773
Total Base Number (mg KOH/g)	7.8

Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website. The contents of this data sheet is given in good faith but without warranty.