

HC-ANA-SIG

Intelligent sensor reader



**HC-ANA-SIG
Class 0**



**HC-ANA-SIG with integrated temperature,
moisture and illumination sensors**

TECHNICAL SPECIFICATIONS

- IP67. Specially designed for wall installation and for underground manhole installation (flat antenna). IP68 available
- Automatic connection to data server. Sensor level data sent to remote software application every X minutes, Y hours or daily
- Automatic updating of internal data from server. Downlink mode
- Battery power 2xAAA. Low power (power save function available)
- Available with AC/DC trafo included
- 3 analog/digital inputs to read temperature, light, moisture, noise, doors etc. sensors, meters pulses etc. + 1 extra input only for digital input sensors
- Analog inputs can be configured with up to 2 limit values to send alarms when the voltage read is below or above the limits
- Up to 100 Hz for pulses inputs
- SIGFOX connection. Any infrastructure needed. Zone 1, 2 and 4
- Magnet detector to activate, send packet and Downlink mode
- Memory 128 kbytes
- RTC/Calendar with alarms. Time self-adjustment
- Easy configuration from WC-1553, PC app or by Downlink
- Up to 15 year battery life
- * Devices can be delivered with temperature, moisture, light, noise, etc. sensors pre-installed in the device