

## HC-ANA-SIG

### Intelligent sensor reader



HC-ANA-SIG  
Class 0



HC-AMBIENT-SIG with integrated temperature,  
moisture and illumination sensors

#### TECHNICAL SPECIFICATIONS

- IP67. Specially designed for wall installation and for underground manhole installation (flat antenna). IP68 available
  - Automatic connection to data server. Sensor level data sent to remote software application every X minutes, Y hours or daily
  - Automatic updating of internal data from server. Downlink mode
  - Battery power 2xAAA. Low power (power save function available)
  - Available with AC/DC internal trafo or 6-24VDC power included
  - 3 analog/digital inputs to read temperature, light, moisture, noise, doors etc. sensors, meters pulses etc. + 1 extra input only for digital input sensors
  - Analog inputs can be configured with up to 2 limit values to send alarms when the voltage read is below or above the limits
  - Up to 100 Hz for pulses inputs
  - SIGFOX connection. Any infrastructure needed. Zone 1, 2, 4 and 7
  - Magnet detector to activate, send packet and Downlink mode
  - Memory 128 kbytes
  - RTC/Calendar with alarms. Time self-adjustment
  - Easy configuration from PC app (USB Configurator) or by Downlink
  - Up to 15 year battery life
- \* Devices can be delivered with temperature, moisture, light, noise, etc. sensors pre-installed in the device