



QUICK
SHIP

BLACKJACK[®]
L I G H T I N G

QUICK SHIP PROGRAM

SEPTEMBER • 2020

Blackjack maintains a core group of products for rapid fulfillment. Individual fixtures are typically available to ship within two weeks (though may vary for large quantities). Systems are normally available within six weeks.

Offerings update frequently. Visit blackjacklighting.com for most up-to-date listings.


CIRCUIT



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
CIR-43P-WH-27U-30K	43"	White	120 W	7680 Lm	30K
CIR-32P-WH-27U-30K	32"	White	92 W	4680 Lm	30K
CIR-24P-WH-27U-30K	24"	White	42 W	3280 Lm	30K

CCT Options: 2700K, 3500K, 4000K
Input Voltage: 120-277V
Universal Dimming: 0-10V, TRIAC, ELV


AERO



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
ARO-25P-SW-27U-30K	25"	Satin Nickel / White	26.7 W	1895 Lm	30K
ARO-25P-BG-27U-30K	25"	Black / Brushed Gold	26.7 W	1895 Lm	30K

Input Voltage: 120-277V
Universal Dimming: 0-10V, TRIAC, ELV

FLAIR



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
FLR-48L-BL-27U-30K	48"	Black	21 W	2000 Lm	30K
FLR-48L-WH-27U-30K	48"	White	21 W	2000 Lm	30K

CCT Options: 2700K, 3500K, 4000K
Input Voltages: 120-277V
Dimming: 0-10V, TRIAC, ELV

STEELOS



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
STL-38P-BL-27U-30K	38"	Matte Black	30 W	1948 Lm	30K

Input Voltage: 120-277V
Universal Dimming: 0-10V, TRIAC, ELV

PILLBOX



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
SP-PBX-SO-10-BG-NAK-E26-SP5	10"	Black/Gold	NA	NA	NA
SP-PBX-FR-10-BG-30K-16W-SP5	10"	Black/Gold	13 W	680 Lm	30K
SP-PBX-SO-10-WG-NAK-E26-SP5	10"	White/Gold	NA	NA	NA
SP-PBX-FR-10-WG-30K-16W-SP5	10"	White/Gold	13 W	680 Lm	30K

Optional LED Light Kit

CCT Options: 2700K, 3500K, 4000K
 Input Voltage: 120-277V
 Universal Dimming: 0-10V, TRIAC, ELV

SO = E-26 Socket (bulb not included)
 FR = Frosted diffuser with integrated light kit
 single pendant configuration with
 5" canopy and integrated driver

DOMOS



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
SP-DOM-SO-16-RW-NAK-E26-SP5	16"	Brass/White	NA	NA	NA
SP-DOM-SO-16-SW-NAK-E26-SP5	16"	Satin Nickel /White	NA	NA	NA
SP-DOM-SO-16-WG-NAK-E26-SP5	16"	White/Gold	NA	NA	NA

Optional LED Light Kit

CCT Options: 2700K, 3500K, 4000K
 Input Voltage: 120-277V
 Universal Dimming: 0-10V, TRIAC, ELV

SO = E26 Socket (bulb not included)
 FR = Frosted diffuser with integrated light kit
 single pendant configuration with
 5" canopy and integrated driver

NOVO TALL



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
SP-NVT-RR-02-BL-30K-5W-SP5	18"	Black	5 W	400 Lm	30K
SP-NVT-LR-02-BL-30K-5W-SP5	18"	Black	5 W	400 Lm	30K
SP-NVT-RR-02-PC-30K-5W-SP5	18"	Polished Chrome	5 W	400 Lm	30K
SP-NVT-LR-02-PC-30K-5W-SP5	18"	Polished Chrome	5 W	400 Lm	30K

CCT Options: 2700K, 3500K, 4000K
 Input Voltage: 120-277V
 Universal Dimming: 0-10V, TRIAC, ELV

RR = Reflector Ring
 LR = Luminous Ring Diffuser
 (both) single pendant configuration with
 5" canopy and integrated driver

NOVO SHORT



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
SP-NVS-LR-02-BL-30K-5W-SP5	3"	Black	5 W	400 Lm	30K
SP-NVS-LR-02-PC-30K-5W-SP5	3"	Polished Chrome	5 W	400 Lm	30K
SP-NVS-RR-02-BL-30K-5W-SP5	3"	Black	5 W	400 Lm	30K
SP-NVS-RR-02-PC-30K-5W-SP5	3"	Polished Chrome	5 W	400 Lm	30K

CCT Options: 2700K, 3500K, 4000K
 Input Voltage: 120-277V
 Universal Dimming: 0-10V, TRIAC, ELV

RR = Reflector Ring
 LR = Luminous Ring Diffuser
 (both) single pendant configuration with
 5" canopy and integrated driver

PENDANTS

AVAILABLE WITHIN 2 WEEKS

**QUICK
SHIP**

SHORT FROSTED



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
SP-LGD-SF-01-BL-30K-3W-SP5	1"	Black	3 W	170 Lm	30K
SP-LGD-SF-01-PC-30K-3W-SP5	1"	Polished Chrome	3 W	170 Lm	30K

CCT Options: 2700K, 3500K, 4000K
Input Voltage: 120-277V
Universal Dimming: 0-10V, TRIAC, ELV

Single pendant configuration with 5" canopy and integrated driver

TALL CLEAR



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
SP-LGD-TC-01-BL-30K-3W-SP5	1"	Black	3 W	170 Lm	30K
SP-LGD-TC-01-PC-30K-3W-SP5	1"	Polished Chrome	3 W	170 Lm	30K

CCT Options: 2700K, 3500K, 4000K
Input Voltage: 120-277V
Universal Dimming: 0-10V, TRIAC, ELV

Single pendant configuration with 5" canopy and integrated driver

GLOBE FROSTED



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
SP-GLS-FR-03-BL-30K-3W-SP5	3"	Black	3 W	170 Lm	30K
SP-GLS-FR-03-PC-30K-3W-SP5	3"	Polished Chrome	3 W	170 Lm	30K

CCT Options: 2700K, 3500K, 4000K
Input Voltage: 120-277V
Universal Dimming: 0-10V, TRIAC, ELV

Single pendant configuration with 5" canopy and integrated driver

TASK LAMPS


FLEXI TASK LAMP



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
FLX-06T-BK-22D-30K	6"	Black	8W	480 Lm	30K
FLX-06T-WH-22D-30K	6"	White	8W	480 Lm	30K

Input Voltages: 120-220VAC
Dimming: Three step dimming


MILO



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
MLO-24V-SN-12T-30K	24"	Satin Nickel	21 W	1140 Lm	30K
MLO-36V-SN-12T-30K	36"	Satin Nickel	21 W	1300 Lm	30K

CCT Options: 2700K, 3500K, 4000K
Input Voltages: 120V
Dimming: TRIAC

NANO



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
NAN-25V-PC-12T-30K	24"	Polished Chrome	22 W	1040 Lm	30K
NAN-36V-PC-12T-30K	36"	Polished Chrome	28 W	1280 Lm	30K

CCT Options: 2700K, 3500K, 4000K
Input Voltages: 120V
Dimming: TRIAC

SCONCES

MILO



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
MLO-21S-SN-12T-30K	14"	Satin Nickel	12 W	890 Lm	30K

CCT Options: 2700K, 3500K, 4000K
Input Voltages: 120V
Dimming: TRIAC

NANO



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
NAN-14S-PC-12T-30K	14"	Polished Chrome	14 W	757 Lm	30K

CCT Options: 2700K, 3500K, 4000K
Input Voltages: 120V
Dimming: TRIAC

FLUSH MOUNTS

NANO



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
NAN-12F-SN-12T-30K	12"	Satin Nickel	21 W	1000 Lm	30K


Input Voltage: 120V
Universal Dimming: TRIAC

QUATRO SYSTEM

Square Configuration

AVAILABLE WITHIN 6 WEEKS

QUICK
SHIP



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
MSQ-2425-BL-XXX-4S-XX-30K	4' SQUARE	Black	148W	8,200 Lm	30K
MSQ-2425-BL-XXX-6S-XX-30K	6' SQUARE	Black	333W	18,450 Lm	30K
MSQ-2425-BL-XXX-8S-XX-30K	8' SQUARE	Black	592W	32,800 Lm	30K

CCT Options: 2700K, 3500K, 4000K
Input Voltage: 120-277V
Universal Dimming: 0-10V, TRIAC, ELV

QUATRO SYSTEM ORDERING GUIDE


Family	Size/Type	Finish	Pendant	Layout	Pattern	CCT.
MSQ	2425 2425 24"/ 25 Port	BL BL Matte Black	LSF Short Frosted LTC Tall Clear GSF 3" Frosted Globe	45 2x2 Square 65 3x3 Square 85 4x4 Square	LV LEVEL RA RANDOM	30K 3000K

Additional Quick Ship system options may be available, consult factory

Example: MSQ-2425-BL-LSF-4S-LV-30K

QUATRO SYSTEM

Linear Configuration



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
MSQ-2425-BL-XXX-4L-XX-30K	4' LINEAR	Black	74W	4,100 Lm	30K
MSQ-2425-BL-XXX-6L-XX-30K	6' LINEAR	Black	111W	6,150 Lm	30K
MSQ-2425-BL-XXX-8L-XX-30K	8' LINEAR	Black	148W	8,200 Lm	30K

CCT Options: 2700K, 3500K, 4000K
Input Voltage: 120-277V
Universal Dimming: 0-10V, TRIAC, ELV

QUATRO SYSTEM ORDERING GUIDE

Family	Size/Type	Finish	Pendant	Layout	Pattern	CCT.
MSQ	2425 2425 24"/ 25 Port	BL BL Matte Black	LSF Short Frosted LTC Tall Clear GSF 3" Frosted Globe	4L 1x2 Linear 6L 1x3 Linear 8L 1x4 Linear	LV LEVEL RA RANDOM	30K 3000K

Additional Quick Ship system options may be available, consult factory


Example: MSQ-2425-BL-LSF-4L-LV-30K

DUO SYSTEM

Linear Configuration

AVAILABLE WITHIN 6 WEEKS

QUICK
SHIP



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
MSD-3818-BL-XXX-6L-XX-30K	6' LINEAR	Black	61W	3,896 Lm	30K
MSD-3818-BL-XXX-9L-XX-30K	9' LINEAR	Black	93W	5,844 Lm	30K
MSD-3818-BL-XXX-12L-XX-30K	12' LINEAR	Black	122W	37,792 Lm	30K

CCT Options: 2700K, 3500K, 4000K
Input Voltage: 120-277V
Universal Dimming: 0-10V, TRIAC, ELV

DUO SYSTEM ORDERING GUIDE


Family	Size/Type	Finish	Pendant	Layout	Pattern	CCT.
MSD	3818 3818 38"/ 18 Port	BL BL Matte Black	LSF Short Frosted LTC Tall Clear GSF 3" Frosted Globe	6L 1x2 Linear 9L 1x3 Linear 12L 1x4 Linear	LV LEVEL RA RANDOM	30K 3000K

Additional Quick Ship system options may be available, consult factory

Example: MSD-3818-BL-LSF-6L-LV-30K

SOLO SYSTEM

Linear Configuration



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
MSS-4811-BL-XXX-4L-XX-30K	4' LINEAR	Black	25W	990Lm	30K
MSS-4811-BL-XXX-8L-XX-30K	8' LINEAR	Black	50W	1,980 Lm	30K
MSS-4811-BL-XXX-12L-XX-30K	12' LINEAR	Black	75W	2,970 Lm	30K

CCT Options: 2700K, 3500K, 4000K
Input Voltage: 120-277V
Universal Dimming: 0-10V, TRIAC, ELV

Driver located in end feed compartment

SOLO SYSTEM ORDERING GUIDE

Family	Size/Type	Finish	Pendant	Layout	Pattern	CCT.
MSL	4811 4811 48"/ 11 Port	BL BL Matte Black	LSF Short Frosted LTC Tall Clear GSF 3" Frosted Globe NSL Novo Short-Luminous Ring NTL Novo Tall-Luminous Ring	4L 1x1 Linear 8L 1x2 Linear 12L 1x3 Linear	LV LEVEL RA RANDOM	30K 3000K

Additional Quick Ship system options may be available, consult factory

Example: MSL-4811-BL-LSF-4L-LV-30K

BLACKJACK[®]
L I G H T I N G

BLACKJACKLIGHTING.COM

CORPORATE

1547 BARCLAY BLVD.
BUFFALO GROVE, IL 60089
PHONE: (847) 941-0588
FAX: (847) 306-3432

