

QUICK
SHIP



BLACKJACK[®]
L I G H T I N G

QUICK SHIP PRODUCT
OCTOBER 2020 VERSION

Blackjack maintains a core group of products for rapid fulfillment. Individual fixtures are typically available to ship within two weeks (though may vary for large quantities). Systems are normally available within six weeks.

Offerings update frequently. Visit blackjacklighting.com for most up-to-date listings.

PENDANTS

AVAILABLE WITHIN 2 WEEKS

QUICK SHIP


CIRCUIT



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
CIR-43P-WH-27U-__K*	43"	White	120 W	7680 Lm	Varies
CIR-32P-WH-27U-__K*	32"	White	92 W	4680 Lm	Varies
CIR-24P-WH-27U-__K*	24"	White	42 W	3280 Lm	Varies

*Select CCT: 27K (2700K), 30K (3000K), 35K (3500K), 40K (4000K)
 Input Voltage: 120-277V
 Dimming: Universal (0-10V, TRIAC, ELV)

AERO



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
ARO-25P-SW-27U-30K	25"	Satin Nickel / White	26.7 W	1895 Lm	30K
ARO-25P-BG-27U-30K	25"	Black / Brushed Gold	26.7 W	1895 Lm	30K

CCT: 30K (3000K)
 Input Voltage: 120-277V
 Dimming: Universal (0-10V, TRIAC, ELV)

FLAIR



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
FLR-48L-BL-27U-__K*	48"	Black	21 W	2000 Lm	Varies
FLR-48L-WH-27U-__K*	48"	White	21 W	2000 Lm	Varies

*Select CCT: 27K (2700K), 30K (3000K), 35K (3500K), 40K (4000K)
 Input Voltage: 120-277V
 Dimming: Universal (0-10V, TRIAC, ELV)

STEELOS



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
STL-38P-BL-27U-30K	38"	Matte Black	30 W	1948 Lm	30K

CCT: 30K (3000K) standard. Additional CCT options available as special order. Contact us for availability.
 Input Voltage: 120-277V
 Dimming: Universal (0-10V, TRIAC, ELV)

PENDANTS

AVAILABLE WITHIN 2 WEEKS

QUICK SHIP

PILLBOX



	PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
E26	PBX-10P-BG-12E-NAK	10"	Black/Gold	NA	NA	NA
	PBX-10P-WG-12E-NAK	10"	White/Gold	NA	NA	NA
E26 Socket: Socket only (Bulb not included) Input Voltage: 120V				E26 Version - 5" canopy		
LED	PBX-10P-BG-27U-__K*	10"	Black/Gold	13 W	680 Lm	Varies
	PBX-10P-WG-27U-__K*	10"	White/Gold	13 W	680 Lm	Varies
*Select CCT: 27K (2700K), 30K (3000K), 35K (3500K), 40K (4000K) Input Voltage: 120-277V Dimming: Universal (0-10V, TRIAC, ELV)				LED Version - Frosted diffuser, LED light kit, with 5" canopy and integrated driver		

DOMOS



	PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
E26	DOM-16P-RW-12E-NAK	16"	Brass/White	NA	NA	NA
	DOM-16P-SW-12E-NAK	16"	Satin Nickel / White	NA	NA	NA
	DOM-16P-WG-12E-NAK	16"	White/Gold	NA	NA	NA
E26 Socket: Socket only (Bulb not included) Input Voltage: 120V				E26 Version - 5" canopy		
LED	DOM-16P-RW-27U-__K*	16"	Brass/White	16 W	900 Lm	Varies
	DOM-16P-SW-27U-__K*	16"	Satin Nickel / White	16 W	900 Lm	Varies
	DOM-16P-WG-27U-__K*	16"	White/Gold	16 W	900 Lm	Varies
*Select CCT: 27K (2700K), 30K (3000K), 35K (3500K), 40K (4000K) Input Voltage: 120-277V Dimming: Universal (0-10V, TRIAC, ELV)				LED Version - Frosted diffuser, LED light kit, with 5" canopy and integrated driver		

NOVO TALL



	PART NUMBER	HEIGHT	FINISH	POWER	OUTPUT	CCT.
	MNTR-02P-BL-27U-30K	18.75"	Black	5 W	400 Lm	30K
	MNTL-02P-BL-27U-30K	19.25"	Black	5 W	400 Lm	30K
	MNTR-02P-PC-27U-30K	18.75"	Polished Chrome	5 W	400 Lm	30K
	MNTL-02P-PC-27U-30K	19.25"	Polished Chrome	5 W	400 Lm	30K
CCT: 30K (3000K) standard. Additional CCT options available as special order. Contact us for availability. Input Voltage: 120-277V Dimming: Universal (0-10V, TRIAC, ELV)				MNTR = Reflector Ring MNTL = Luminous Ring Diffuser (both) single pendant configuration with 5" canopy and integrated driver		

NOVO SHORT



	PART NUMBER	HEIGHT	FINISH	POWER	OUTPUT	CCT.
	MNSL-02P-BL-27U-30K	4.25"	Black	5 W	400 Lm	30K
	MNSL-02P-PC-27U-30K	4.25"	Polished Chrome	5 W	400 Lm	30K
	MNSR-02P-BL-27U-30K	3.75"	Black	5 W	400 Lm	30K
	MNSR-02P-PC-27U-30K	3.75"	Polished Chrome	5 W	400 Lm	30K
CCT: 30K (3000K) standard. Additional CCT options available as special order. Contact us for availability. Input Voltage: 120-277V Dimming: Universal (0-10V, TRIAC, ELV)				MNSR = Reflector Ring MNSL = Luminous Ring Diffuser (both) single pendant configuration with 5" canopy and integrated driver		

PENDANTS

AVAILABLE WITHIN 2 WEEKS

QUICK SHIP

SHORT FROSTED



PART NUMBER	HEIGHT	FINISH	POWER	OUTPUT	CCT.
MLSF-01P-BL-27U-30K	3"	Black	2 W	90 Lm	30K
MLSF-01P-PC-27U-30K	3"	Polished Chrome	2 W	90 Lm	30K

CCT: 30K (3000K) standard. Additional CCT options available as special order. Contact us for availability.
 Input Voltage: 120-277V
 Dimming: Universal (0-10V, TRIAC, ELV)

Single pendant configuration with 5" canopy and integrated driver

TALL CLEAR



PART NUMBER	HEIGHT	FINISH	POWER	OUTPUT	CCT.
MLTC-01P-BL-27U-30K	7"	Black	2 W	90 Lm	30K
MLTC-01P-PC-27U-30K	7"	Polished Chrome	2 W	90 Lm	30K

CCT: 30K (3000K) standard. Additional CCT options available as special order. Contact us for availability.
 Input Voltage: 120-277V
 Dimming: Universal (0-10V, TRIAC, ELV)

Single pendant configuration with 5" canopy and integrated driver

GLOBE FROSTED



PART NUMBER	HEIGHT	FINISH	POWER	OUTPUT	CCT.
MGSF-03P-BL-27U-30K	5"	Black	2 W	90 Lm	30K
MGSF-03P-PC-27U-30K	5"	Polished Chrome	2 W	90 Lm	30K

CCT: 30K (3000K) standard. Additional CCT options available as special order. Contact us for availability.
 Input Voltage: 120-277V
 Dimming: Universal (0-10V, TRIAC, ELV)

Single pendant configuration with 5" canopy and integrated driver

TASK LAMPS

FLEXI TASK LAMP



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
FLX-06T-BK-22D-30K	6" Dia.	Black	8W	480 Lm	30K
FLX-06T-WH-22D-30K	6" Dia.	White	8W	480 Lm	30K


Input Voltages: 120-277VAC
 Dimming: Three step dimming

VANITIES

AVAILABLE WITHIN 2 WEEKS

QUICK SHIP


MILO



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
MLO-24V-SN-12T-__K*	24"	Satin Nickel	21 W	1140 Lm	Varies
MLO-36V-SN-12T-__K*	36"	Satin Nickel	21 W	1300 Lm	Varies

*Select CCT: 27K (2700K), 30K (3000K), 35K (3500K), 40K (4000K)
 Input Voltage: 120V standard. 120-277V available as special order.
 Dimming: TRIAC standard. Additional dimming options available as special order.

NANO



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
NAN-25V-PC-12T-__K*	24"	Polished Chrome	22 W	1040 Lm	Varies
NAN-36V-PC-12T-__K*	36"	Polished Chrome	28 W	1280 Lm	Varies

*Select CCT: 27K (2700K), 30K (3000K), 35K (3500K), 40K (4000K)
 Input Voltage: 120V standard. 120-277V available as special order.
 Dimming: TRIAC standard. Additional dimming options available as special order.

SCONCES

MILO



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
MLO-14S-SN-12T-__K*	14"	Satin Nickel	12 W	890 Lm	Varies

*Select CCT: 27K (2700K), 30K (3000K), 35K (3500K), 40K (4000K)
 Input Voltage: 120V standard. 120-277V available as special order.
 Dimming: TRIAC standard. Additional dimming options available as special order.

NANO



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
NAN-14S-PC-12T-__K*	14"	Polished Chrome	14 W	757 Lm	Varies

*Select CCT: 27K (2700K), 30K (3000K), 35K (3500K), 40K (4000K)
 Input Voltage: 120V standard. 120-277V available as special order.
 Dimming: TRIAC standard. Additional dimming options available as special order.

FLUSH MOUNTS

NANO



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
NAN-12F-SN-12T-30K	12"	Satin Nickel	21 W	1000 Lm	30K


Input Voltage: 120V
 Dimming: TRIAC

QUATRO SYSTEM

Square Configuration

AVAILABLE WITHIN 6 WEEKS

QUICK SHIP



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
MSQ-2425-BL-XXX-4S-XX-30K	4' SQUARE	Black	148W	8,200 Lm	30K
MSQ-2425-BL-XXX-6S-XX-30K	6' SQUARE	Black	333W	18,450 Lm	30K
MSQ-2425-BL-XXX-8S-XX-30K	8' SQUARE	Black	592W	32,800 Lm	30K

CCT: 30K (3000K) standard. Additional CCT options available as special order. Contact us for availability.
Input Voltage: 120-277V
Dimming: Universal (0-10V, TRIAC, ELV)

QUATRO SYSTEM ORDERING GUIDE

Family	Size/Type	Finish	Pendant	Layout	Pattern	CCT.
MSQ	2425	BL				30K
	2425 24"/25 Port	BL Matte Black	LSF Short Frosted LTC Tall Clear GSF 3" Frosted Globe	4S 2x2 Square 6S 3x3 Square 8S 4x4 Square	LV LEVEL RA RANDOM	30K 3000K

Approved submittal drawings are required for systems. Quick ship timing is based on receipt of purchase order, deposit and signed submittal.


Example: MSQ-2425-BL-LSF-4S-LV-30K

DUO SYSTEM

Linear Configuration

AVAILABLE WITHIN 6 WEEKS

QUICK SHIP



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
MSD-3818-BL-XXX-6L-XX-30K	6' LINEAR	Black	61W	3,896 Lm	30K
MSD-3818-BL-XXX-9L-XX-30K	9' LINEAR	Black	93W	5,844 Lm	30K
MSD-3818-BL-XXX-12L-XX-30K	12' LINEAR	Black	122W	37,792 Lm	30K

CCT: 30K (3000K) standard. Additional CCT options available as special order. Contact us for availability.
Input Voltage: 120-277V
Dimming: Universal (0-10V, TRIAC, ELV)

DUO SYSTEM ORDERING GUIDE


Family	Size/Type	Finish	Pendant	Layout	Pattern	CCT.
MSD	3818	BL				30K
	3818 38"/18 Port	BL Matte Black	LSF Short Frosted LTC Tall Clear GSF 3" Frosted Globe	6L 1x2 Linear 9L 1x3 Linear 12L 1x4 Linear	LV LEVEL RA RANDOM	30K 3000K

Approved submittal drawings are required for systems. Quick ship timing is based on receipt of purchase order, deposit and signed submittal.

Example: MSD-3818-BL-LSF-6L-LV-30K

QUATRO SYSTEM

Linear Configuration



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
MSQ-2425-BL-XXX-4L-XX-30K	4' LINEAR	Black	74W	4,100 Lm	30K
MSQ-2425-BL-XXX-6L-XX-30K	6' LINEAR	Black	111W	6,150 Lm	30K
MSQ-2425-BL-XXX-8L-XX-30K	8' LINEAR	Black	148W	8,200 Lm	30K

CCT: 30K (3000K) standard. Additional CCT options available as special order. Contact us for availability.
Input Voltage: 120-277V
Dimming: Universal (0-10V, TRIAC, ELV)

QUATRO SYSTEM ORDERING GUIDE


Family	Size/Type	Finish	Pendant	Layout	Pattern	CCT.
MSQ	2425	BL				30K
	2425 24"/25 Port	BL Matte Black	LSF Short Frosted LTC Tall Clear GSF 3" Frosted Globe	4L 1x2 Linear 6L 1x3 Linear 8L 1x4 Linear	LV LEVEL RA RANDOM	30K 3000K

Approved submittal drawings are required for systems. Quick ship timing is based on receipt of purchase order, deposit and signed submittal.

Example: MSQ-2425-BL-LSF-4L-LV-30K

SOLO SYSTEM

Linear Configuration



PART NUMBER	SIZE	FINISH	POWER	OUTPUT	CCT.
MSL-4811-BL-XXX-4L-XX-30K	4' LINEAR	Black	25W	990Lm	30K
MSL-4811-BL-XXX-8L-XX-30K	8' LINEAR	Black	50W	1,980 Lm	30K
MSL-4811-BL-XXX-12L-XX-30K	12' LINEAR	Black	75W	2,970 Lm	30K

CCT: 30K (3000K) standard. Additional CCT options available as special order. Contact us for availability. **Driver located in end feed compartment**
Input Voltage: 120-277V
Dimming: Universal (0-10V, TRIAC, ELV)

SOLO SYSTEM ORDERING GUIDE

Family	Size/Type	Finish	Pendant	Layout	Pattern	CCT.
MSL	4811	BL				30K
	4811 48"/11 Port	BL Matte Black	LSF Short Frosted LTC Tall Clear GSF 3" Frosted Globe NSL Novo Short-Luminous Ring NTL Novo Tall-Luminous Ring	4L 1x1 Linear 8L 1x2 Linear 12L 1x3 Linear	LV LEVEL RA RANDOM	30K 3000K

Approved submittal drawings are required for systems. Quick ship timing is based on receipt of purchase order, deposit and signed submittal.

Example: MSL-4811-BL-LSF-4L-LV-30K

BLACKJACK[®]
L I G H T I N G

BLACKJACKLIGHTING.COM

CORPORATE

1547 BARCLAY BLVD.
BUFFALO GROVE, IL 60089
PHONE: (847) 941-0588
FAX: (847) 306-3432

