


CD-10

PRODUCT PARAMETERS	UNIT	CD-10
Pixel pitch	mm	10
LED		Nationstar SMD 2727 3 in 1 (White)
Application		Fixed Install
Ingress protection	IP	IP 66 - fanless
Brightness	cd/sqm	5,500 Nits calibrated
Color temperature	K	6500
Viewing angle (50% brightness)	deg.	H: 110 / V: 110
Mask		Mask with contrast enhancing shaders
Module size (WxHxD)	mm	400x400x68
Pixel matrix per cabinet (WxH)	Px	40x40
Pixel density	Px/sqm	10.000
Weight per module	Kg	2.8
Cabinet material		PC+10%GF (UL94V0 + UV optimized/aluminium)
Maintenance mode		Front and rear access
Grey scale	bit	14
Brightness control	Level	256
Processing depth	bit	16
Colors		4.39 trillion
Display refresh rate	Hz	960
Scan rate		1/6
Contrast ratio		10000 : 1
Input voltage	VAC	110-240 VAC
Power per cabinet	W	Max 110W / typical 40W
Video frame rate	Hz	<60 Hz
Calibration		Color calibration on the white, brightness on RGB
Lifetime (50% brightness)	H	50.000
Operating humidity		10 - 95%
Operating temperature		-20°C / +60°C
Screen uniformity correction		Yes
Certification		CE
Certification		EMC Class A



Modular



Plug and Play




Lightweight



Safety Eyelet



Completely Sealed



Connected



No fans



No Sender Box



Power efficient



Upgrade




Calibrated



Proof of Display



Unique Panel ID



Easy access



Unified Cable