

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name**

KABRIC Floor Smooth Prepare Comp A

**Product no.**

-

**REACH registration number**

Not applicable

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Paint

**Uses advised against**

-

The full text of any mentioned and identified use categories are given in section 16

### 1.3. Details of the supplier of the safety data sheet

**Company and address**

Flügger Denmark A/S  
Islevdalvej 151  
DK-2610 Rødovre  
Tlf. +45 70 15 15 05  
www.detalecph.com

**Contact person****E-mail**

hello@detalecph.com

**SDS date**

2021-07-08

**SDS Version**

2.0

### 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Skin Irrit. 2; H315  
Skin Sens. 1; H317  
Eye Irrit. 2; H319  
Aquatic Chronic 2; H411  
See full text of H-phrases in section 2.2.

### 2.2. Label elements

**Hazard pictogram(s)****Signal word**

Warning

**Hazard statement(s)**

Causes skin irritation. (H315)

According to EC-Regulation 2015/830

May cause an allergic skin reaction. (H317)  
 Causes serious eye irritation. (H319)  
 Toxic to aquatic life with long lasting effects. (H411)

#### ▼ Precautionary statements

**General** If medical advice is needed, have product container or label at hand. (P101).  
 Keep out of reach of children. (P102).  
**Prevention** Avoid release to the environment. (P273).  
 Wear protective gloves/protective clothing/eye protection/face protection. (P280).  
**Response** IF ON SKIN: Wash with plenty of water and soap. (P302+P352).  
 If skin irritation occurs: Get medical advice/attention. (P332+P313).  
**Storage** -  
**Disposal** Dispose of contents/container to an approved waste disposal plant. (P501).

#### Identity of the substances primarily responsible for the major health hazards

2,2-Bis(p-(2,3-epoxypropoxy)phenyl)propane; Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.; Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2); Bisphenol F-(epichlorhydrin), reaction product

#### Additional labelling

Contains epoxy constituents. May produce an allergic reaction. (EUH205)

#### Unique formula identifier (UFI)

-

#### 2.3. Other hazards

When mixing two components, consult the safety data sheets for both components.

#### Additional warnings

Not applicable

#### ▼ VOC (volatile organic compound)

VOC-Max: 10 g/l, MAXIMUM VOC CONTENT (A/j (SB)): 500 g/l.

## SECTION 3: Composition/information on ingredients

### 3.1/3.2. Substances/Mixtures

NAME: 2,2-Bis(p-(2,3-epoxypropoxy)phenyl)propane  
 IDENTIFICATION NOS.: CAS-no: 1675-54-3 EC-no: 216-823-5 REACH-no: 01-2119456619-26  
 CONTENT: 70-80%  
 CLP CLASSIFICATION: Skin Irrit. 2, Skin Sens. 1, Eye Irrit. 2, Aquatic Chronic 2  
 H315, H317, H319, H411  
 NOTE: H

NAME: Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.  
 IDENTIFICATION NOS.: CAS-no: 68609-97-2 EC-no: 271-846-8 REACH-no: 01-2119485289-22 Index-no: 603-103-00-4  
 CONTENT: 10 - <15%  
 CLP CLASSIFICATION: Skin Irrit. 2, Skin Sens. 1  
 H315, H317  
 NOTE: H

NAME: Bisphenol F-(epichlorhydrin), reaction product  
 IDENTIFICATION NOS.: CAS-no: 9003-36-5 EC-no: 500-006-8 REACH-no: 01-2119454392-40  
 CONTENT: 1 - <5%  
 CLP CLASSIFICATION: Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2  
 H315, H317, H411  
 NOTE: H

NAME: Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)  
 IDENTIFICATION NOS.: CAS-no: 933999-84-9 EC-no: 618-939-5 REACH-no: 01-2119463471-41  
 CONTENT: 1 - <5%  
 CLP CLASSIFICATION: Skin Irrit. 2, Skin Sens. 1, Eye Irrit. 2, Aquatic Chronic 3  
 H315, H317, H319, H412

(\*) See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

H = Epoxy resin

#### Other information

Eye Cat. 2 Sum = Sum(Ci/S(G)CLi) = 12,2 - 18,3

Skin Cat. 2 Sum = Sum(Ci/S(G)CLi) = 13,4 - 20,1

N chronic (CAT 2) Sum = Sum(Ci/(M(chronic)\*25)\*0.1\*10^CATi) = 2,48 - 3,72

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Bring the person into fresh air and stay with him/her.

#### Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with soap and water. Skin cleanser can be used. DO NOT use solvents or thinners.

#### Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure to flush under the upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

#### Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

#### Burns

Not applicable

### 4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

### ▼ 4.3. Indication of any immediate medical attention and special treatment needed

If skin irritation occurs: Get medical advice/attention.

#### Information to medics

Bring this safety data sheet.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

### 5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities. It is recommended to install waste collection trays to prevent emissions to the waste water system and surrounding environment.

### 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

## SECTION 7: Handling and storage

### ▼7.1. Precautions for safe handling

Individuals suffering from eczema and individuals with excessively sweaty palms (hyperhidrosis manuum) should not work with the product.

Do not smoke, eat or drink in the working premises. Special working clothes must not be worn during meal breaks. Eye wash equipment must be available. Wash hands before breaks, before using restroom facilities and at the end of work. The work should be organized and performed in such a way that skin contact is avoided. Use means of protection till the product is fully cured.

### 7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Storage temperature

Store frost-free.

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### OEL

No substances are listed in The Control of Substances Hazardous to Health Regulations with an occupational exposure limit.

#### DNEL / PNEC

DNEL (2,2-Bis(p-(2,3-epoxypropoxy)phenyl)propane): 12,25 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2,2-Bis(p-(2,3-epoxypropoxy)phenyl)propane): 12,25 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects - Workers

DNEL (2,2-Bis(p-(2,3-epoxypropoxy)phenyl)propane): 8,33 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2,2-Bis(p-(2,3-epoxypropoxy)phenyl)propane): 8,33 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Short term – Systemic effects - Workers

DNEL (Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.): 3,6 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.): 1 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.): 870 µg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.): 500 µg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.): 500 µg/kg bw/day

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Bisphenol F-(epichlorhydrin), reaction product): 29,39 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Bisphenol F-(epichlorhydrin), reaction product): 104,15 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Bisphenol F-(epichlorhydrin), reaction product): 8,7 mg/m<sup>3</sup>

Exposure: Inhalation

According to EC-Regulation 2015/830

Duration of Exposure: Long term – Systemic effects - General population  
DNEL (Bisphenol F-(epichlorhydrin), reaction product): 62,5 mg/kg bw/day  
Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population  
DNEL (Bisphenol F-(epichlorhydrin), reaction product): 6,25 mg/kg bw/day  
Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)): 10,57 mg/m3

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects

DNEL (Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)): 10,57 mg/m3

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects

DNEL (Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)): 0,44 mg/m3

Exposure: Inhalation

Duration of Exposure: Long term – Local effects

DNEL (Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)): 6 mg/kg

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects

DNEL (Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)): 0,0226 mg/cm2

Exposure: Dermal

Duration of Exposure: Short term – Local effects

DNEL (Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)): 0,0226 mg/cm2

Exposure: Dermal

Duration of Exposure: Long term – Local effects

PNEC (2,2-Bis(p-(2,3-epoxypropoxy)phenyl)propane): 3 µg/l

Exposure: Freshwater

PNEC (2,2-Bis(p-(2,3-epoxypropoxy)phenyl)propane): 10 mg/l

Exposure: Sewage Treatment Plant

PNEC (2,2-Bis(p-(2,3-epoxypropoxy)phenyl)propane): 0,3 µg/l

Exposure: Marine water

PNEC (2,2-Bis(p-(2,3-epoxypropoxy)phenyl)propane): 0,5 mg/kg dw

Exposure: Freshwater sediment

PNEC (2,2-Bis(p-(2,3-epoxypropoxy)phenyl)propane): 0,5 mg/kg dw

Exposure: Marine water sediment

PNEC (2,2-Bis(p-(2,3-epoxypropoxy)phenyl)propane): 0,013 mg/l

Exposure: Intermittent release

PNEC (Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.): 7,2 µg/l

Exposure: Freshwater

PNEC (Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.): 720 ng/l

Exposure: Marine water

PNEC (Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.): 10 mg/l

Exposure: Sewage Treatment Plant

PNEC (Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.): 307,16 mg/kg dw

Exposure: Freshwater sediment

PNEC (Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.): 30,72 mg/kg dw

Exposure: Marine water sediment

PNEC (Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.): 61,42 mg/kg dw

Exposure: Soil

PNEC (Bisphenol F-(epichlorhydrin), reaction product): 3 µg/l

Exposure: Freshwater

PNEC (Bisphenol F-(epichlorhydrin), reaction product): 300 ng/l

Exposure: Marine water

PNEC (Bisphenol F-(epichlorhydrin), reaction product): 10 mg/l

Exposure: Sewage Treatment Plant

PNEC (Bisphenol F-(epichlorhydrin), reaction product): 294 µg/kg dw

Exposure: Freshwater sediment

PNEC (Bisphenol F-(epichlorhydrin), reaction product): 29,4 µg/kg dw

Exposure: Marine water sediment

PNEC (Bisphenol F-(epichlorhydrin), reaction product): 237 µg/kg dw

Exposure: Soil

PNEC (Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)): 0,001 mg/l

Exposure: Marine water

PNEC (Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)): 0,283 mg/kg

Exposure: Freshwater sediment

PNEC (Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)): 0,028 mg/kg

Exposure: Marine water sediment

PNEC (Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)): 1 mg/l

Exposure: Sewage Treatment Plant

PNEC (Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)): 0,223 mg/kg

According to EC-Regulation 2015/830

Exposure: Soil  
 PNEC (Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)): 0,011 mg/l  
 Exposure: Freshwater

## 8.2. Exposure controls

Control is unnecessary if the product is used as intended.

### General recommendations

Observe general occupational hygiene standards.

### Exposure scenarios

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

### Exposure limits

Occupational exposure limits have not been defined for the substances in this product.

### Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

### Measures to avoid environmental exposure

Keep containment materials near the workplace. If possible, collect spillage during work.

## Individual protection measures, such as personal protective equipment



### Generally

Use only CE marked protective equipment.

### Respiratory Equipment

Dust, which is unhealthy, is produced when treated surfaces are grinded. Use respiratory protection if necessary (P2, EN 143).

### Skin protection

Use suitable protective clothing, for example overalls made of polypropylene or work clothes made of cotton/polyester.

### Hand protection

Recommended: Nitrile rubber (EN 374)

Breakthrough time: See the manufacturer's instructions.

### Eye protection

Recommended: In the likelihood of direct or incidental exposure, use face protection. (EN 166)

## SECTION 9: Physical and chemical properties

### ▼ 9.1. Information on basic physical and chemical properties

Form	Liquid
Colour	Colourless
Odour	Characteristic
Odour threshold (ppm)	No data available.
pH	< 11,5
Viscosity (40°C)	No data available.
Density (g/cm <sup>3</sup> )	1,13
<b>Phase changes</b>	
Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.
<b>Data on fire and explosion hazards</b>	
Flash point (°C)	200
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.

### Solubility

Solubility in water

n-octanol/water coefficient

Insoluble

No data available.

### 9.2. Other information

Solubility in fat (g/L)

Blandingsforhold

No data available.

Komp. A 6,5kg / Komp. B 3,5kg

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

Hardening time at 15 °C: 5-7 days.

### 10.3. Possibility of hazardous reactions

Nothing special

### 10.4. Conditions to avoid

Nothing special

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

No data available.

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/irritation

Causes serious eye irritation.

#### Respiratory or skin sensitisation

May cause an allergic skin reaction.

#### Germ cell mutagenicity

No data available.

#### Carcinogenicity

No data available.

#### Reproductive toxicity

No data available.

#### STOT-single exposure

No data available.

#### STOT-repeated exposure

No data available.

#### Aspiration hazard

No data available.

#### Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

## SECTION 12: Ecological information

### 12.1. Toxicity

Substance: Bisphenol F-(epichlorhydrin), reaction product

Species: Scenedesmus capricornutum

Test: EC50

Duration: 72 h

Result: 1,8 mg/l

Substance: 2,2-Bis(p-(2,3-epoxypropoxy)phenyl)propane

Species: Fish

Test: LC50

According to EC-Regulation 2015/830

Duration: 96h  
Result: 1,3 mg/l

### 12.2. Persistence and degradability

**Substance**  
Reaction products of hexane-1,...

**Biodegradability**  
Yes

**Test**  
Closed Bottle Test

**Result**  
47%

### 12.3. Bioaccumulative potential

**Substance**  
Reaction products of hexane-1,...

**Potential bioaccumulation**  
No

**LogPow**  
No data available

**BCF**  
3,57

### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

### 12.6. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

#### Waste

**EWC code**  
08 01 11\*

waste paint and varnish containing organic solvents or other dangerous substances

#### Specific labelling

Not applicable

#### Contaminated packing

Contaminated packaging must be disposed of similarly to the product.

## SECTION 14: Transport information

### 14.1 – 14.4

This product is within scope of the regulations of transport of dangerous goods.

Additional information:

ADR 3.3.1 375. These substances when carried in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG 2.10.2.7. Marine Pollutants packaged in single or combination packagings containing a net quantity per single of inner packaging of 5lt or less for liquids or having a net mass per single of inner packaging of 5kg or less for solids are not subject to any other provisions of this Code relevant to marine pollutants provided the packagings meet the general requirements of 4.1.1.1, 4.1.1.2, and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria of inclusion in another hazards class all provisions of the Code relevant to any additional hazards continue to apply.

#### ADR/RID

<b>14.1. UN number</b>	3082
<b>14.2. UN proper shipping name</b>	-
<b>14.3. Transport hazard class(es)</b>	9
<b>14.4. Packing group</b>	III
<b>Notes</b>	-
<b>Tunnel restriction code</b>	E

#### IMDG

<b>UN-no.</b>	3082
<b>Proper Shipping Name</b>	Environmentally hazardous substance, liquid, n.o.s. (Epoxy resin).
<b>Class</b>	9
<b>PG*</b>	III



<b>EmS</b>	F-A-S-F
<b>MP**</b>	>5L
<b>Hazardous constituent</b>	-
<b>IATA/ICAO</b>	
<b>UN-no.</b>	3082
<b>Proper Shipping Name</b>	Environmentally hazardous substance, liquid, n.o.s. (Epoxy resin).
<b>Class</b>	9
<b>PG*</b>	III

#### 14.5. Environmental hazards

-

#### 14.6. Special precautions for user

-

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(\*) Packing group

(\*\*) Marine pollutant

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

##### Demands for specific education

Use of this product requires dedicated training in work with polyurethane and epoxy products.

##### Additional information

Not applicable

##### Seveso

Seveso III Part 1: E2

##### Biocidal reg. no.

Not applicable

##### Sources

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.  
 Directive 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC.  
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).  
 Regulation (EC) 1907/2006 (REACH).  
 The Control of Major Accident Hazards (COMAH) Regulations 2015.

#### 15.2. Chemical safety assessment

No

### SECTION 16: Other information

#### Full text of H-phrases as mentioned in section 3

H315 - Causes skin irritation.  
 H317 - May cause an allergic skin reaction.  
 H319 - Causes serious eye irritation.  
 H411 - Toxic to aquatic life with long lasting effects.  
 H412 - Harmful to aquatic life with long lasting effects.

#### The full text of identified uses as mentioned in section 1

-

#### Additional label elements

Not applicable

#### Other

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The classification of the mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

**The safety data sheet is validated by**

ELGR

**Date of last essential change**

**(First cipher in SDS version)**

2021-03-11(1.0)

**Date of last minor change**

**(Last cipher in SDS version)**

2021-03-11