



**DETALE
CPH**

EDGE

Monochromatic simplicity unites nature and urban lifestyle.



Del dit DETALE-projekt ^{DK}

Del dit helt eget DETALE projekt eller find massevis af inspiration i andres projekter på Instagram under #detalecph. Vi modtager meget gerne billeder til deling på hello@detalecph.com

Del ditt DETALE-prosjekt ^{NO}

Del ditt helt eget DETALE prosjekt eller finn masse inspirasjon i andres prosjekter på instagram under #detalecph. Vi vil gjerne motta bilder som vi kan dele, på hello@detalecph.com

Dela ditt DETALE-projekt ^{SE}

Dela ditt helt eget DETALE-projekt eller hitta massor av inspiration i andras projekt på instagram under #detalecph. Vi tar gärna emot bilder för delning på hello@detalecph.com

Share your DETALE-project ^{UK}

Share your DETALE project or find lots of inspiration from other projects on instagram #detalecph. We are happy to receive pictures to share at hello@detalecph.com



You will need

EDGE wallpaper
Adhesive suitable for non-woven wallpaper
Utility knife
Paint roller
Wallpaper brush
Measuring tape
Sponge or cloth and warm water
Shielding e.g. plastic or cardboard

Preparation

To achieve a nice result, it is important that the wall is smooth. If the surface is not smooth it should be smoothed entirely with filler and then primed. Regular painted walls should just be washed and primed before EDGE is installed.

If you currently have wallpaper, glass tissue, concrete or plaster, you can read in our FAQ about how best to prepare your surface. EDGE FAQ can be found in the 'How To' section on our website detalecph.com.

Designs

For the two designs Modern Moscow and Sassy Stockholm, you should be aware of what is called 'offset fit'. This means you must make sure that the pattern fits together, every time you install a new piece of wallpaper. For the design Cosy Copenhagen, we also recommend making sure the pattern continues for each strip of wallpaper you install.

Your EDGE surface can be washed carefully with a cloth or sponge and warm water if necessary.

1

Plan out your project before you begin and determine where you will install the first strip of wallpaper. Measure your wall so you know how long the wallpaper should be. It is a good idea to add 5-10 cm to the length of the strip to ensure that it is long enough. Then, apply adhesive directly on the wall, going beyond the width of the strip of wallpaper. It is important that the entire area the wallpaper is to be applied to is covered with adhesive. The wall should not be dripping from adhesive, but the thickness of the layer should be sufficient for the wallpaper to be well attached to the wall.

2

Apply the first strip of EDGE wallpaper by holding it up on the wall against the edge of the ceiling. Gently brush the wallpaper against the wall, using a suitable wallpaper brush. Start from the centre and work your way outwards towards the edges. Make sure that there are no air bubbles trapped under the wallpaper and avoid getting any adhesive on the front side of the wallpaper.

Should any adhesive end up on the front side of the wallpaper it can be removed with a damp cloth with clean, warm water. Excess adhesive should be removed while it is still wet.

When the strip of wallpaper is well attached to the wall you can cut away excess wallpaper along the top- and bottom edges with a utility knife.

Tip: Hold a filling knife up against the wall so you have something to cut along, to achieve a sharp and straight result. Make sure you always have a fresh, sharp blade on your utility knife.

3

Repeat the process strip by strip until you have covered the entire wall. The individual strips of wallpaper should be fitted directly next to one another, without any gaps and without overlapping.

Any leftover adhesive squeezed up between the wallpaper strips during the installation should be removed with a damp cloth with clean, warm water. Make sure to remove excess adhesive before it dries.

detalecph.com

@detalecph

hello@detalecph.com