



Model SRT UTV Fire Skid and Storage System Specifications



A Division of MTECH, Inc.
1072 Marauder, Suite 210
Chico, CA 95973
1.888.797.5100
www.qtacfire.com
www.mtechincorporated.com



TANK

The tank shall have the following characteristics:

- QTAC PolyTough™ extrusion-welded Copolymer Polypropylene construction
- Capacity of 40 gallons of water
 - OPTION: Capacities of 50 or 60 gallons optional at no extra charge
- 3/8" internal baffles with interlocking design to meet NFPA standards
- Pump suction plumbed to the center of the tank with anti-cavitation device
- 1-1/2" tank drain
- 4" vented fill tower
- Site tube to gauge water level
- Flange-mounted anchor points to secure the skid unit to the bed
- Integrated tank features adjustable side rails to facilitate mounting of side storage boxes or trays
- OPTION: Forklift runners

PUMP & ENGINE

The pump system shall have the following characteristics:

- Honda GXH50 2.2hp engine with recoil start and low oil sensor with Koshin 1-1/2" self-priming centrifugal pump (61 PSI Max; 73 GPM Max)
 - OPTION: Honda GX200 5.5hp engine with recoil start and low oil sensor with Waterax Versax 6 2" self-priming centrifugal pump (120 PSI Max; 105 GPM Max)
- 1-1/2" auxiliary suction (Koshin)
 - OPTION: Draft hose kit
- 2" auxiliary suction (Waterax)
 - OPTION: Draft hose kit
 - OPTION: 2" NST Suction
- 1" discharge
 - OPTION: 1-1/2" NST Discharge
- 1" gated discharge to hose reel
- 2" gated tank to pump
- 1" gated pump to tank return / fill
- All plumbing to be of either composite polypropylene, brass, or stainless steel



STORAGE BOXES

The storage boxes shall have the following characteristics:

- QTAC PolyTough™ extrusion-welded Copolymer Polypropylene construction
- Approximately 6.2 cubic feet of storage area
- QTAC sleek hinge doors with recessed gas shocks
- Stainless steel locking latches

FOAM

The foam system shall have the following characteristics:

- OPTION: End-of-line foam system, includes:
 - Aerating nozzle
 - ¼ turn end-of-line shut-off
- With Honda GX200 5.5hp equipped QTAC
 - OPTION: Around-the-pump foam system, includes:
 - MTECH PolyTough™ extrusion-welded Copolymer Polypropylene construction 2.5-gallon external foam reservoir
 - Threaded 6" fill well, flush mounted at top of tank with vented cap
 - Adjustable through-the-pump foam proportioner
 - Aerating nozzle

HOSE & ASSOCIATED COMPONENTS

The hose and associated hardware shall have the following characteristics:

- 3/4" X 50' of rubber booster hose
 - OPTION: 3/4" X 75' of rubber booster hose
 - OPTION: 3/4" X 100' of rubber booster hose
 - OPTION: 3/4" X 50' Red rubber booster hose kit
- Hannay electric rewind hose reel
- Nozzle Options:
 - Max 8 GPM brass bulls-eye with 1/4-turn shut off
 - Max 15 GPM D-ring fire-style nozzle
 - Max 18 GPM Vari-Nozzle



- 10-23 GPM Viper Nozzle
 - OPTION: Pistol grip bale shut off

WEIGHTS*

Dry weight, 40-Gallon Tank, Koshin SEH-40H: 415 lbs.

Wet weight, 40-Gallon Tank, Koshin SEH-40H: 750 lbs.

Dry weight, 40-Gallon Tank, Waterax Versax 6: 445 lbs.

Wet weight, 40-Gallon Tank, Waterax Versax 6: 779 lbs.

Additional weight per component:

- Around-the-Pump Foam
 - 2.5-gallon
 - Dry Weight: 7 lbs.
 - Wet Weight: 28 lbs.

**All weights are approximate*

